

LAGUNA

Saareke 60, 800 m³/h

Design

8034122349367



*The photograph is purely for information
It may not correspond to the selected version.*

OMINAISUUDET

Reunaimu
Elektroniset kytkimet
LED-valaistus
Metalliset rasvasuodattimet, irroitettavat ja pestävät
Aktiivihiilisuodatin vakiovarusteena
Himmennettävä LED valaistus
Säädettävä LED valosävy (2700 - 5600 K)

Paneloitu versio (Asiakkaan oma muotoilu)
From 04.11.2024 the dynamic and dimmable light is included.

OPTIONAL ACCESSORIES

KACL.815
RST puhdistuspyyhkeet
KACL.887#F
White glass - Island 60 cm
KACL.887#N
Black glass - Island 60 cm

TECHNICAL FEATURES

Installation type
Saareke
Dimensions
60 cm
Viimeistelystä
Kiillotettu ruostumaton teräs (AISI 304)
Musta karkaistu lasi
Valkoinen karkaistu lasi
Saatavana omavalintaisella paneelilla
Motor
800 m³/h
Type of control
Elektroniset kytkimet
Speed settings
3 + boost
Lighting
Led 4x1,2 W - 2700 K / 5600 K
Filter
2 x Metallic filter "Base" - 235x245 mm (spare part)
Charcoal filter
Pyöreä aktiivihiilisuodatin Ø170mm
- Type 6 (included)

: 60 cm
: 52 cm

PACKAGING: WEIGHTS AND VOLUMES


36 kg
30 kg
0.39 m³
1035 mm
510 mm
740 mm

CONSUMPTION AND CONNECTION FEATURES

280 W
220-240V
50-60Hz
Shuko

MOTOR TECHNICAL SHEET

670 m³/h
I.E.C. 61591
67 dB(A)re1pW
I.E.C.60704-2-13
500 Pa
215 W
B



LAGUNA


Saareke 60, 800 m³/h

Design

8034122349367

MOTOR TECHNICAL SHEET

Speed motor	1	2	3	4
dB(A)re1pW-I.E.C.60704-2-13	49	55	61	67
(m ³ /h) I.E.C.61591	270	360	470	670
	390	420	460	500
	134	156	180	215
	150	150	150	150




LAGUNA

Saareke 60, 800 m³/h

Design

8034122349367



PF		
S	Falmec Spa	
M	Saareke 60, 800 m ³ /h	
AEC	65,6	kWh/a
EEC	B	
FDE	25,5	
FDEC	B	
LE	28,4	
LEC	A	
GFE	53,0	
GFEC	F	
Qmin	270,0	m ³ /h
Qmax	470,0	m ³ /h
Qboost	670,0	m ³ /h
SPEmin	49	dBa
SPEmax	61	dBa
SPEboost	67	dBa
PO	-	W
PS	0,48	W
PI		
F	1,1	
EEL	64,8	
Qbep	333,0	m ³ /h
Pbep	407	Pa
Qboost	670,0	m ³ /h
Wbep	147,7	W
WL	8,60	W
Emiddle	245	lux
Lwa-SPEmax	61	dBa

PF_Product fiche according to 65/2014 S_Supplier name / M_Model identification / AEC_Annual Energy Consumption (AEC hood) / EEC_Energy Efficiency class / FDE_Fluid Dynamic Efficiency (FDE hood) / FDEC_Fluid Dynamic Efficiency class / LE_Lighting Efficiency (LE hood) / LEC_Lighting Efficiency class / GFE_Grease Filtering Efficiency / GFEC_Grease Filtering Efficiency class / Qmin_Air flow (in m³/h) at min speed in normal use / Qmax_Air flow (in m³/h) at max speed in normal use / Qboost_Air flow (in m³/h) at intensive or boost setting (max air-flow) / SPEmin_Airborne acoustical A-weighted sound power emissions at min speed in normal use / SPEmax_Airborne acoustical A-weighted sound power emissions at max speed in normal use / SPEboost_Airborne acoustical A-weighted sound power emissions (in dB) at intensive or boost setting / PO_Power consumption in off mode (Po) / Ps_Power consumption in stand by mode (Ps). **PI_Additional information according to 66/2014** F_Time increase factor / EEL_Energy Efficiency Index / Qbep_Measured air flow rate at best efficiency point / Pbep_Measured air pressure at best efficiency point / Qboost_Maximum air flow / Wbep_Measured electric power input at best efficiency point / WL_Nominal power of the lighting system / Emiddle_Average illumination of the lighting system on the cooking surface / Lwa=SPEmax_Sound pressure level at the highest speed.