

LUMEN

Version

Wall 90 cm - 800 m3/h

Collection

DESIGNER SERIES - Design

EAN code

8034122324876



The photograph is purely for information
It may not correspond to the selected version.


FEATURES

- Scotch brite stainless steel (AISI 304)
- Electronic controls
- LED lighting
- Air Falmec filter for balanced suction
- Charcoal filter included
- Dialogue system

Strip led 4000°K from 12.28.21;
Dialogue system from 03.04.24

OPTIONAL ACCESSORIES

- EW1300**
Remote under-roof motor 1300 m3/h
- EW1500**
Outdoor extractor fan 1500 m3/h
- IN950**
Remote under-roof motor 950 m3/h
- KACL.510#I**
Extension H700 - Wall
- KACL.512#I**
Extension H960 - Wall
- KACL.770#41F**
Remote under-roof 1100 m3/h
Brushless
- KACL.786#41F**
Outdoor extractor fan 1000 m3/h
- KACL.815**
Protective cleaning cloths for stainless steel (box 10 pcs)



TECHNICAL FEATURES

- Installation type**
Wall
- Dimensions**
90 cm
- Finishing**
Scotch brite stainless steel (AISI 304)
- Motor**
800 m³/h
- Type of control**
Electronic controls
- Speed settings**
4
- Lighting**
Strip led (4000K)
- Filter**
3 x Metallic filter "Air Falmec" - Wall 285x301 mm
- Charcoal filter**
Square charcoal filter - Type 3 (optional)
- Minimum distance**
Gas hob: 63 cm
Electric hob: 52 cm

PACKAGING:WEIGHTS AND VOLUMES

- Gross weight**
24 kg
- Net weight**
19 kg
- Volumes**
0.25 m³
- Packaging size**
Length 995 mm
Height 430 mm
Depth 595 mm

CONSUMPTION AND CONNECTION FEATURES

- Maximum consumption**
320 W
- Voltage**
220-240V
- Frequency**
50-60Hz
- Plug type**
Shuko

MOTOR TECHNICAL SHEET

- Maximum capacity**
680 m³/h
I.E.C. 61591
- Maximum sound level**
68 dB(A)re1pW
I.E.C.60704-2-13
- Maximum pressure (Pa)**
500 Pa
- Maximum motor power**
215 W

LUMEN

Version

Wall 90 cm - 800 m3/h

Collection

DESIGNER SERIES - Design

EAN code

8034122324876

MOTOR TECHNICAL SHEET

Motor speed	1	2	3	4
Sound level dB(A)re1pW-I.E.C.60704-2-13	49	56	62	68
Capacity (m3/h) I.E.C.61591	280	370	480	680
Maximum pressure (Pa)	390	420	480	500
Motor Power (W)	132	153	175	215
Air outlet	150	150	150	150

CAPACITY / PRESSURE

