falmec

ZENITH NRS

Version

Collection
NRS Collection


EAN code
8034122354873

FEATURES

NRS technology for a quieter kitchen
Electronic control
LED lighting
Metallic grease filter, removable and washable
Combined Carbon.Zeo filter, regenable
Optional remote control
Central stripe made in brilliant steel
Tempered glass shelf
Diffuse illumination

OPTIONAL ACCESSORIES

KACL.400
Silent / Conveyor NRS
KACL.815
Protective cleaning cloths for stainless steel (box 10 pcs)
KACL.961
Charcoal and Zeolite filter
101078898
High Performance Filter
105080053
Remote control



TECHNICAL FEATURES

Installation type
Wall
Dimensions
120 cm
Finishing
Scotch brite stainless steel (AISI 304)
Tempered glass
Motor
800 m³/h
Type of control
Electronic control
Speed settings
4
Filter
Metallic filter - Zenith Island
Charcoal filter
Charcoal and Zeolite filter (optional)
Minimum distance
Gas hob: 60 cm
Electric hob: 52 cm

PACKAGING:WEIGHTS AND VOLUMES

ZENITH NRS Gross weight
31 kg
Net weight
25 kg
Volumes
0.42 m³
Packaging size
Length
1070 mm
Height
450 mm
Depth
870 mm
GLASS KIT 120 cm **Gross weight**
32.5 kg
Net weight
21 kg
Volumes
0.13 m³
Packaging size
Length
1270 mm
Height
180 mm
Depth
565 mm

CONSUMPTION AND CONNECTION FEATURES

Voltage
220-240V
Frequency
50-60Hz
Plug type
Shuko

MOTOR TECHNICAL SHEET

Maximum capacity
610 m³/h
I.E.C. 61591
Maximum noise level
54,5 dB(A)re1pW
I.E.C.60704-2-13
Maximum pressure (Pa)
510 Pa
Max. motor power
224 W
ENERGY CLASS
C

falmec

ZENITH NRS

Version


Collection
NRS Collection

EAN code
8034122354873

MOTOR TECHNICAL SHEET

Motor speed	1	2	3	4
Noise level dB(A)re1pW-I.E.C.60704-2-13	37	41	46	54,5
Capacity (m3/h) I.E.C.61591	220	290	375	610
Maximum pressure (Pa)	390	440	490	510
Motor Power (W)	130	150	178	224
Air outlet	150	150	150	150

CAPACITY / PRESSURE



falmec


ZENITH NRS

Version

Collection
NRS Collection

EAN code
8034122354873

ENERGY LABEL



PF		
S	Falmec Spa	
M		
AEC	88,0	kWh/a
EEC	C	
FDE	28,9	
FDEC	A	
LE	9,7	
LEC	E	
GFE	76,0	
GFEC	C	
Qmin	220,0	m³/h
Qmax	375,0	m³/h
Qboost	610,0	m³/h
SPEmin	37	dBa
SPEmax	46	dBa
SPEboost	55	dBa
PO	-	W
PS	0,48	W
PI		
F	1	
EEI	74,8	
Qbep	369,0	m³/h
Pbep	369	Pa
Qboost	610,0	m³/h
Wbep	131,0	W
WL	55,00	W
Emiddle	532	lex
Lwa-SPEmax	46	dBa

PF_Product fiche according to 65/2014 S_Supplier name / M_Model identification / AEC_Annual Energy Consumption (AEC hood) / EEC_Energy Efficiency class / FDE_Fluid Dynamic Efficiency (FDE hood) / FDEC_Fluid Dynamic Efficiency class / LE_Lighting Efficiency (LE hood) / LEC_Lighting Efficiency class / GFE_Grease Filtering Efficiency / GFEC_Grease Filtering Efficiency class / Qmin_Air flow (in m³/h) at min speed in normal use / Qmax_Air flow (in m³/h) at max speed in normal use / Qboost_Air flow (in m³/h) at intensive or boost setting (max air-flow) / SPEmin_Airborne acoustical A-weighted sound power emissions at min speed in normal use / SPEmax_Airborne acoustical A-weighted sound power emissions at max speed in normal use / SPEboost_Airbone acoustical A-weighted sound power emissions (in dB) at intensive or boost setting / P0_Power consumption in off mode (Po) / Ps_Power consumption in stand by mode (Ps). **PI_Additional information according to 66/2014** F_Time increase factor / EEI_Energy Efficiency Index / Qbep_Measured air flow rate at best efficiency point / Pbep_Measured air pressure at best efficiency point / Qboost_Maximun air flow / Wbep_Measured electric power input at best efficiency point / WL_Nominal power of the lighting system / Emiddle_Average illumination of the lighting system on the cooking surface / Lwa=SPEmax_Sound pressure level at the highest speed.