

## DOWN DRAFT

### Version

Remote under-roof 1100 m<sup>3</sup>/h  
Brushless

### Collection

Design+

### EAN code

8034122348551



## FEATURES

Perimeter suction  
Touch control + 24 h function  
LED lighting  
Optional combined regenaleble  
Carbon.Zeo filter  
Optional remote control

Panoramic hobs are recommended with this hood.

### OPTIONAL ACCESSORIES

#### KACL.815

Protective cleaning cloths for stainless steel (box 10 pcs)

## TECHNICAL FEATURES

**Installation type**  
Worktop  
**Dimensions**  
120 cm cm  
**Finishing**  
Scotch brite stainless steel (AISI 304)  
Black tempered glass  
**Type of control**  
Touch control  
**Speed settings**  
4  
**Lighting**  
Led stripe  
**Filter**  
2 x Metallic filter "Top" - 404x216 mm  
**Charcoal filter**  
Kit filters Carbon.Zeo (optional)

## PACKAGING:WEIGHTS AND VOLUMES

### DOWN DRAFT Gross weight

52.6 kg

### Net weight

43.2 kg

### Volumes

0.43 m<sup>3</sup>

### Packaging size

Length

1395 mm

Height

355 mm

Depth

865 mm

### REMOTE MOTOR Remote

under-roof 1100 m<sup>3</sup>/h

Brushless **Gross weight**

9.2 kg

### Net weight

8 kg

### Volumes

0.06 m<sup>3</sup>

### Packaging size

Length

435 mm

Height

340 mm

Depth

385 mm

## CONSUMPTION AND CONNECTION FEATURES

### Maximum consumption

30 W

### Voltage

220-240V

### Frequency

50-60Hz

### Plug type

Shuko

## MOTOR TECHNICAL SHEET

### Maximum capacity

680 m<sup>3</sup>/h

I.E.C. 61591

### Maximum noise level

66 dB(A)re1pW

I.E.C.60704-2-13

### Maximum pressure (Pa)

400 Pa

### Max. motor power

200 W

### ENERGY CLASS

## DOWN DRAFT

### Version

Remote under-roof 1100 m<sup>3</sup>/h  
Brushless

### Collection

Design+

### EAN code

8034122348551

## MOTOR TECHNICAL SHEET

Motor speed	1	2	3	4
Noise level dB(A)re1pW-I.E.C.60704-2-13	51	57	64	66
Capacity (m <sup>3</sup> /h) I.E.C.61591	330	430	580	680
Maximum pressure (Pa)	460	400	400	400
Motor Power (W)	40	80	130	200
Air outlet	150	150	150	150