

NUBE

Version

Ceiling 90 cm - Inox

Collection

Design+

EAN code

8034122355405

KACL.782#49F

Slim motor 800 m³/h

Collection

Accessoires

EAN code

8034122708584



*The photograph is purely for information
It may not correspond to the selected version.*

FEATURES

Scotch brite stainless steel (AISI 304)

Perimeter suction

Electronic control

Metallic grease filter, removable and washable

Remote control included

Cut-out size: 505 x 940 mm

OPTIONAL ACCESSORIES

KACL.815

Protective cleaning cloths for stainless steel (box 10 pcs)

KACL.782#49F

Slim motor 800 m³/h

KACL.798#41F

Remote under-roof motor 950 m³/h

KACL.770#41F

Remote under-roof 1100 m³/h

Brushless

KACL.786#41F

Outdoor extractor fan 1000 m³/h

KACL.796#4AF

Outdoor extractor fan 1500 m³/h

KACL.797#4AF

Remote under-roof motor 1300 m³/h

KACL.939#BF

Ceiling re-circulation filtering kit (only for Slim Motor)

TECHNICAL FEATURES

Installation type

Ceiling

Dimensions

90 cm

Finishing

Scotch brite stainless steel (AISI 304)

Type of control

Electronic control

Speed settings

4

Lighting

No lighting

Filter

Metallic filter "Base" - 290x267 mm - 2 pz

PACKAGING:WEIGHTS AND VOLUMES

NUBE

Ceiling 90 cm - Inox

Gross weight

23.30 kg

Net weight

20.50 kg

Volume

0.14 m³

Packaging size

Length

1120 mm

Height

670 mm

Depth

190 mm

REMOTE MOTOR

Slim motor 800 m³/h

Gross weight

10.00 kg

Net weight

9.00 kg

Volumes

0.04 m³

Packaging size

Length

550 mm

Height

370 mm

Depth

175 mm

CONSUMPTION AND CONNECTION FEATURES

Voltage / Frequency

220-240V

50-60Hz

Plug type

Shuko

MOTOR TECHNICAL SHEET

Maximum capacity

680 m³/h

I.E.C. 61591

Maximum noise level

68 dB(A)re1pW

I.E.C.60704-2-13

Maximum pressure (Pa)

490 Pa

Max. motor power

239 W

NUBE

KACL.782#49F
Slim motor 800 m³/h

Version
Ceiling 90 cm - Inox

Collection
Accessoires

Collection
Design+

EAN code
8034122708584

EAN code
8034122355405

MOTOR TECHNICAL SHEET

Motor speed	1	2	3	4
Noise level dB(A)re1pW-I.E.C.60704-2-13	52	60	65	68
Capacity (m3/h) I.E.C.61591 Normalized Pipes	330	470	580	680
Maximum pressure (Pa)	420	460	470	490
Motor Power (W)	158	177	194	239
Air outlet	220x90220x90220x90220x90			

CAPACITY / PRESSURE

