

DOWN DRAFT

Version

Remote under-roof 1100 m³/h
Brushless

Collection

Design+

EAN code

8034122348100



*The photograph is purely for information
It may not correspond to the selected version.*

FEATURES

Perimeter suction
Touch control + 24 h function
Top filter, removable and washable
Optional combined regenerable Carbon.Zeo filter
Optional remote control

Panoramic hobs are recommended with this hood.

OPTIONAL ACCESSORIES

KACL.815

Protective cleaning cloths for stainless steel (box 10 pcs)

TECHNICAL FEATURES

Installation type
Worktop
Dimensions
90 cm
Finishing
Scotch brite stainless steel (AISI 304)
Black tempered glass
Type of control
Touch control
Speed settings
4
Lighting
Led stripe
Filter
2 x Metallic filter "Top" - 254x216 mm
Charcoal filter
Kit filters Carbon.Zeo (optional)

PACKAGING:WEIGHTS AND VOLUMES

DOWN DRAFT Gross weight

44 kg

Net weight

37 kg

Volumes

0.34 m³

Packaging size

Length

1070 mm

Height

370 mm

Depth

870 mm

REMOTE MOTOR Remote

under-roof 1100 m³/h

Brushless **Gross weight**

9.2 kg

Net weight

8 kg

Volumes

0.06 m³

Packaging size

Length

435 mm

Height

340 mm

Depth

385 mm

CONSUMPTION AND CONNECTION FEATURES

Maximum consumption

30 W

Voltage

220-240V

Frequency

50-60Hz

Plug type

Shuko

MOTOR TECHNICAL SHEET

Maximum capacity

680 m³/h

I.E.C. 61591

Maximum noise level

66 dB(A)re1pW

I.E.C.60704-2-13

Maximum pressure (Pa)

400 Pa

Max. motor power

200 W

ENERGY CLASS

0

DOWN DRAFT

Version

Remote under-roof 1100 m³/h
Brushless

Collection

Design+

EAN code

8034122348100

MOTOR TECHNICAL SHEET

Motor speed	1	2	3	4
Noise level dB(A)re1pW-I.E.C.60704-2-13	51	57	64	66
Capacity (m ³ /h) I.E.C.61591	330	430	580	680
Maximum pressure (Pa)	460	400	400	400
Motor Power (W)	40	80	130	200
Air outlet	150	150	150	150