

## DOWN DRAFT

### Version

Remote under-roof 1100 m<sup>3</sup>/h  
Brushless

### Collection

Design+

### EAN code

8034122348100



*The photograph is purely for information  
It may not correspond to the selected version.*

## FEATURES

**Perimeter suction**  
**Touch control + 24 h function**  
**Top filter, removable and washable**  
**Optional combined regenerable Carbon.Zeo filter**  
**Optional remote control**

## OPTIONAL ACCESSORIES

**KACL.815**  
Protective cleaning cloths for stainless steel (box 10 pcs)  
**KACL.930**  
Kit filters Carbon.Zeo  
**105080053**  
Remote control

## TECHNICAL FEATURES

**Installation type**  
Worktop  
**Dimensions**  
90 cm  
**Finishing**  
Scotch brite stainless steel (AISI 304)  
Black tempered glass  
**Type of control**  
Touch control  
**Speed settings**  
4  
**Lighting**  
Led stripe  
**Filter**  
2 x Metallic filter "Top" - 254x216 mm  
**Charcoal filter**  
Kit filters Carbon.Zeo (optional)

## PACKAGING:WEIGHTS AND VOLUMES

### DOWN DRAFT Gross weight

44 kg

### Net weight

37 kg

### Volumes

0.34 m<sup>3</sup>

### Packaging size

Length

1070 mm

Height

370 mm

Depth

870 mm

### REMOTE MOTOR Remote

under-roof 1100 m<sup>3</sup>/h

Brushless **Gross weight**

9.2 kg

### Net weight

8 kg

### Volumes

0.06 m<sup>3</sup>

### Packaging size

Length

435 mm

Height

340 mm

Depth

385 mm

## CONSUMPTION AND CONNECTION FEATURES

### Maximum consumption

30 W

### Voltage

220-240V

### Frequency

50-60Hz

### Plug type

Shuko

## MOTOR TECHNICAL SHEET

### Maximum capacity

680 m<sup>3</sup>/h

I.E.C. 61591

### Maximum noise level

66 dB(A)re1pW

I.E.C.60704-2-13

### Maximum pressure (Pa)

400 Pa

### Max. motor power

200 W

## ENERGY CLASS

0

## DOWN DRAFT

### Version

Remote under-roof 1100 m<sup>3</sup>/h  
Brushless

### Collection

Design+

### EAN code

8034122348100

## MOTOR TECHNICAL SHEET

Motor speed	1	2	3	4
Noise level dB(A)re1pW-I.E.C.60704-2-13	51	57	64	66
Capacity (m <sup>3</sup> /h) I.E.C.61591	330	430	580	680
Maximum pressure (Pa)	460	400	400	400
Motor Power (W)	40	80	130	200
Air outlet	150	150	150	150