

SIRIO

Version

Remote under-roof 1100 m³/h
Brushless

Collection

Design+

EAN code

8034122358482



FEATURES

- Touch control
- Metallic grease filter, removable and washable
- Remote control included
- Dynamic LED Light (2700K - 5600K)
- Motor sold separately

OPTIONAL ACCESSORIES

- KACL.770#41F**
Remote under-roof 1100 m3/h
Brushless
- KACL.782#49F**
Slim motor 800 m3/h
- KACL.786#41F**
Outdoor extractor fan 1000 m3/h
- KACL.796#4AF**
Outdoor extractor fan 1500 m3/h
- KACL.798#41F**
Remote under-roof motor 950 m3/h
- KACL.939#BF**
Ceiling re-circulation filtering kit (only for Slim Motor)

TECHNICAL FEATURES

- Installation type
Ceiling
- Dimensions
90 cm
- Finishing
- Type of control
Electronic control
- Speed settings
4
- Lighting
Led 4x3,6 W - 2700 K / 5600 K
- Filter
3 x Metallic filter "Base" - 290x326 mm
- Maximum distance
Gas hob: 150 cm
Electric hob: 150 cm

PACKAGING:WEIGHTS AND VOLUMES

- SIRIO Gross weight**
31.7 kg
- Net weight**
27.8 kg
- Volumes**
0.21 m³
- Packaging size**

- Length
1330 mm
- Height
215 mm
- Depth
725 mm

- REMOTE MOTOR** Remote under-roof 1100 m³/h
Brushless
- Gross weight**

- 9.2 kg
- Net weight**
8 kg
- Volumes**
0.06 m³
- Packaging size**

- Length
435 mm
- Height
340 mm
- Depth
385 mm

CONSUMPTION AND CONNECTION FEATURES

- Maximum consumption**
30 W
- Voltage**
220-240V
- Frequency**
50-60Hz
- ENERGY CLASS**
A


SIRIO

Version
Remote under-roof 1100 m³/h
Brushless

Collection
Design+

EAN code
8034122358482

ENERGY LABEL



PF		
S	Falmec Spa	
M	Remote under-roof 1100 m³/h Brushless	
AEC	37,2	kWh/a
EEC	A	
FDE	36,9	
FDEC	A	
LE	22,9	
LEC	B	
GFE	65,1	
GFEC	D	
Qmin	350,0	m³/h
Qmax	660,0	m³/h
Qboost	850,0	m³/h
SPEmin	50	dBa
SPEmax	64	dBa
SPEboost	68	dBa
PO	-	W
PS	0,48	W
PI		
F	0.7	
EEL	45,6	
Qbep	405,0	m³/h
Pbep	351	Pa
Qboost	850,0	m³/h
Wbep	167,0	W
WL	13,50	W
Emiddle	309	lex
Lwa-SPEmax	64	dBa

PF_Product fiche according to 65/2014 S_Supplier name / M_Model identification / AEC_Annual Energy Consumption (AEC hood) / EEC_Energy Efficiency class / FDE_Fluid Dynamic Efficiency (FDE hood) / FDEC_Fluid Dynamic Efficiency class / LE_Lighting Efficiency (LE hood) / LEC_Lighting Efficiency class / GFE_Grease Filtering Efficiency / GFEC_Grease Filtering Efficiency class / Qmin_Air flow (in m³/h) at min speed in normal use / Qmax_Air flow (in m³/h) at max speed in normal use / Qboost_Air flow (in m³/h) at intensive or boost setting (max air-flow) / SPEmin_Airborne acoustical A-weighted sound power emissions at min speed in normal use / SPEmax_Airborne acoustical A-weighted sound power emissions at max speed in normal use / SPEboost_Airborne acoustical A-weighted sound power emissions (in dB) at intensive or boost setting / PO_Power consumption in off mode (Po) / Ps_Power consumption in stand by mode (Ps). PI_Additional information according to 66/2014 F_Time increase factor / EEL_Energy Efficiency Index / Qbep_Measured air flow rate at best efficiency point / Pbep_Measured air pressure at best efficiency point / Qboost_Maximun air flow / Wbep_Measured electric power input at best efficiency point / WL_Nominal power of the lighting system / Emiddle_Average illumination of the lighting system on the cooking surface / Lwa=SPEmax_Sound pressure level at the highest speed.