

MOVE

Version
Slide-out 120 cm - white

Collection
DESIGNER SERIES - Design

EAN code
8034122353333



The photograph is purely for information
It may not correspond to the selected version.

FEATURES

Sliding door
Electronic controls
Metallic grease filter,
removable and washable
Optional regenerable
Carbon.zeo filter
Optional chimney
Optional glass shelf
Dimmable led lighting
Dynamic LED Light (2700K -
5600K)

Special order
Availability Carbon.Zeo filter
KACL.961 for hoods produced
from 02.09.2021.
Dimmable led lighting from
11.07.23

OPTIONAL ACCESSORIES

EW1300
Remote under-roof motor 1300
m3/h
EW1500
Outdoor extractor fan 1500 m3/h
IN950
Remote under-roof motor 950
m3/h
KACL.108
Glass shelf 120 cm
KACL.770#41F
Remote under-roof 1100 m3/h
Brushless
KACL.786#41F
Outdoor extractor fan 1000
m3/h
KACL.815
Protective cleaning cloths for
stainless steel (box 10 pcs)
KACL.934
Carbon.Zeo filters
KACL.961
Charcoal and Zeolite filter
KCVJN.00#3
Telescopic chimney h 185 + h 185
KCVJN.01#3
Chimney h 120 mm

TECHNICAL FEATURES

Installation type
Built-in
Dimensions
120 cm
Finishing
Scotch brite stainless steel (AISI
304)
Lower body: finished in black
tempered glass
Motor
800 m³/h
Type of control
Electronic controls
Speed settings
4
Lighting
Led 3x1,2 W - 2700 K / 5600 K
Filter
4 x Metallic filter "Base" -
198x161 mm
Charcoal filter
Charcoal and Zeolite filter
(optional)
Minimum distance
Gas hob: 52 cm
Electric hob: 52 cm

PACKAGING:WEIGHTS AND
VOLUMES


Gross weight
24.1 kg
Net weight
20 kg
Volumes
0.25 m³
Packaging size
Length
1295 mm
Height
410 mm
Depth
465 mm

CONSUMPTION AND
CONNECTION FEATURES


Maximum consumption
280 W
Voltage
220-240V
Frequency
50-60Hz
Plug type
Shuko

MOTOR TECHNICAL SHEET


Maximum capacity
680 m³/h
I.E.C. 61591
Maximum sound level
68 dB(A)re1pW
I.E.C.60704-2-13
Maximum pressure (Pa)
500 Pa
Maximum motor power
215 W



Hood



Optional chimney



Optional shelf

MOVE

Version
Slide-out 120 cm - white

Collection
DESIGNER SERIES - Design

EAN code
8034122353333

MOTOR TECHNICAL SHEET

Motor speed	1	2	3	4
Sound level dB(A)re1pW-I.E.C.60704-2-13	49	56	62	68
Capacity (m3/h) I.E.C.61591	280	370	480	680
Maximum pressure (Pa)	390	420	480	500
Motor Power (W)	132	153	175	215
Air outlet	150	150	150	150

CAPACITY / PRESSURE

