

NUBE

Version

Remote under-roof motor 950 m³/h

Collection

Design+

EAN code

8034122358895

FEATURES

Perimeter suction
Electronic control
Metallic grease filter, removable and washable
Remote control included

OPTIONAL ACCESSORIES

KACL.770#41F
Remote under-roof 1100 m3/h
Brushless

KACL.782#49F
Slim motor 800 m3/h

KACL.786#41F
Outdoor extractor fan 1000 m3/h

KACL.796#4AF
Outdoor extractor fan 1500 m3/h

KACL.797#4AF
Remote under-roof motor 1300 m3/h

KACL.798#41F
Remote under-roof motor 950 m3/h

KACL.939#BF
Ceiling re-circulation filtering kit (only for Slim Motor)

TECHNICAL FEATURES

Installation type
Ceiling

Dimensions
90 cm

Finishing
Painted white steel

Type of control
Electronic control

Speed settings
4

Lighting
No lighting

Filter
3 x Metallic filter "Base" - 290x267 mm

Maximum distance
Gas hob: 150 cm
Electric hob: 150 cm

PACKAGING:WEIGHTS AND VOLUMES

NUBE Gross weight
23.3 kg

Net weight
20.5 kg

Volumes
0.14 m³

Packaging size
Length
1120 mm
Height
190 mm
Depth
670 mm

REMOTE MOTOR Remote under-roof motor 950 m³/h

Gross weight
10 kg

Net weight
9 kg

Volumes
0.06 m³

Packaging size
Length
435 mm
Height
340 mm
Depth
385 mm

CONSUMPTION AND CONNECTION FEATURES

Voltage
220-240V

Frequency
50-60Hz

MOTOR TECHNICAL SHEET

Maximum capacity
830 m³/h
I.E.C. 61591

Maximum noise level
68 dB(A)re1pW
I.E.C.60704-2-13

Maximum pressure (Pa)
580 Pa

Max. motor power
270 W

ENERGY CLASS
0

NUBE

Version
Remote under-roof motor 950
m³/h

Collection
Design+

EAN code
8034122358895

MOTOR TECHNICAL SHEET

Motor speed	1	2	3	4
Noise level dB(A)re1pW-I.E.C.60704-2-13	50	57	64	68
Capacity (m3/h) I.E.C.61591	360	480	630	830
Maximum pressure (Pa)	480	520	560	580
Motor Power (W)	190	220	250	270
Air outlet	150	150	150	150

CAPACITY / PRESSURE

