

## PLANE

### Version

Wall 60 cm - 600 m<sup>3</sup>/h

### Collection

Design

### EAN code

8034122330457



*The photograph is purely for information  
It may not correspond to the selected version.*

## FEATURES

**Scotch brite stainless steel (AISI 304)**  
**Mechanical control**  
**LED lighting**  
**Air Falmec filter for balanced suction**  
**Charcoal filter included**

## OPTIONAL ACCESSORIES

**KACL.510#I**  
 Extension H700 - Wall  
**KACL.512#I**  
 Prolunga H960 - Parete  
**KACL.815**  
 Protective cleaning cloths for stainless steel (box 10 pcs)

## TECHNICAL FEATURES

**Installation type**  
 Wall  
**Dimensions**  
 60 cm  
**Finishing**  
 Scotch brite stainless steel (AISI 304)  
**Motor**  
 600 m<sup>3</sup>/h  
**Type of control**  
 Mechanical control  
**Lighting**  
 Led 2x1,2 W - 3200 K  
**Filter**  
 Metallic filter "Air Falmec" - Wall 278x301 mm - 2 pz  
**Charcoal filter**  
 Square charcoal filter - Type 3 - included  
**Minimum distance**  
 Gas hob: 63 cm  
 Electric hob: 52 cm

## PACKAGING:WEIGHTS AND VOLUMES

**Gross weight**  
 19.00 kg  
**Net weight**  
 16.00 kg  
**Volume**  
 0.19 m<sup>3</sup>  
**Packaging size**  
 Length  
 710 mm  
 Height  
 595 mm  
 Depth  
 450 mm

## CONSUMPTION AND CONNECTION FEATURES

**Maximum consumption**  
 230 W  
**Voltage / Frequency**  
 220-240V  
 50-60Hz  
**Plug type**  
 Shuko

## MOTOR TECHNICAL SHEET

**Maximum capacity**  
 480 m<sup>3</sup>/h  
 I.E.C. 61591  
**Maximum noise level**  
 65 dB(A)re1pW  
 I.E.C.60704-2-13  
**Maximum pressure (Pa)**  
 500 Pa  
**Max. motor power**  
 180 W  
**ENERGY CLASS**  
 C

## PLANE

### Version

Wall 60 cm - 600 m<sup>3</sup>/h

### Collection

Design


### EAN code

8034122330457

## MOTOR TECHNICAL SHEET

Motor speed	1	2	3
Noise level dB(A)re1pW-I.E.C.60704-2-13	49	58	65
Capacity (m3/h) I.E.C.61591 Normalized Pipes	220	320	480
Maximum pressure (Pa)	270	400	500
Motor Power (W)	100	130	180
Air outlet	120	120	120

## CAPACITY / PRESSURE



## PLANE

### Version

Wall 60 cm - 600 m<sup>3</sup>/h


### Collection

Design

### EAN code

8034122330457

## ENERGY LABEL



PF		
S	Falmec Spa	
M	Wall 60 cm - 600 m <sup>3</sup> /h	
AEC	87,7	kWh/a
ECC	C	
FDE	15,8	
FDEC	D	
LE	20,5	
LEC	B	
GFE	80,0	
GFEC	C	
Qmin	220,0	m <sup>3</sup> /h
Qmax	480,0	m <sup>3</sup> /h
Qboost	480,0	m <sup>3</sup> /h
SPEmin	49	dBa
SPEmax	65	dBa
SPEboost	-	dBa
PO	-	W
PS	0,00	W
PI		
F	1,4	
EEl	80,9	
Qbep	303,0	m <sup>3</sup> /h
Pbep	308	Pa
Qboost	480,0	m <sup>3</sup> /h
Wbep	164,0	W
WL	5,30	W
Emiddle	109	lux
Lwa-SPEmax	65	dBa

**PF\_Product fiche according to 65/2014** S\_Supplier name / M\_Model identification / AEC\_Annual Energy Consumption (AEC hood) / EEC\_Energy Efficiency class / FDE\_Fluid Dynamic Efficiency (FDE hood) / FDEC\_Fluid Dynamic Efficiency class / LE\_Lighting Efficiency (LE hood) / LEC\_Lighting Efficiency class / GFE\_Grease Filtering Efficiency / GFEC\_Grease Filtering Efficiency class / Qmin\_Air flow (in m<sup>3</sup>/h) at min speed in normal use / Qmax\_Air flow (in m<sup>3</sup>/h) at max speed in normal use / Qboost\_Air flow (in m<sup>3</sup>/h) at intensive or boost setting (max air-flow) / SPEmin\_Airborne acoustical A-weighted sound power emissions at min speed in normal use / SPEmax\_Airborne acoustical A-weighted sound power emissions at max speed in normal use / SPEboost\_Airborne acoustical A-weighted sound power emissions (in dB) at intensive or boost setting / PO\_Power consumption in off mode (Po) / Ps\_Power consumption in stand by mode (Ps). **PI\_Additional information according to 66/2014** F\_Time increase factor / EEl\_Energy Efficiency Index / Qbep\_Measured air flow rate at best efficiency point / Pbep\_Measured air pressure at best efficiency point / Qboost\_Maximum air flow / Wbep\_Measured electric power input at best efficiency point / WL\_Nominal power of the lighting system / Emiddle\_Average illumination of the lighting system on the cooking surface / Lwa=SPEmax\_Sound pressure level at the highest speed.