falmec

## PRESTIGE

**Version**
Wall 65 cm - Black - 800 m3/h

**Collection**
Design+

**EAN code**
8034122329116



*The photograph is purely for information*
*It may not correspond to the selected version.*

### FEATURES

**Electronic control**
**LED ambient light**
**LED lighting**
**Top filter, removable and washable**
**Charcoal filter included**
**Possible to duct wall mounted from rear**

### OPTIONAL ACCESSORIES

**KACL.770#41F**
Remote under-roof 1100 m3/h Brushless
**KACL.786#41F**
Outdoor extractor fan 1000 m3/h
**KACL.796#4AF**
Outdoor extractor fan 1500 m3/h
**KACL.797#4AF**
Remote under-roof motor 1300 m3/h
**KACL.798#41F**
Remote under-roof motor 950 m3/h
**KACL.815**
Protective cleaning cloths for stainless steel (box 10 pcs)

### TECHNICAL FEATURES

**Installation type**
Wall
**Dimensions**
65 cm
**Finishing**
Scotch brite stainless steel (AISI 304)
Shaped glass and tempered black
**Motor**
800 m³/h
**Type of control**
Electronic control
**Speed settings**
4
**Lighting**
Led 4x1,2 W - 4200 K
**Ambient lighting**
Led strip 7 W - 4200 K
**Filter**
Metallic filter "Top" - 338x216 mm
**Charcoal filter**
Round charcoal filter Ø170 mm - Type 6 (optional)
**Minimum distance**
Gas hob: 60 cm
Electric hob: 52 cm

### PACKAGING:WEIGHTS AND VOLUMES


**Gross weight**
27 kg
**Net weight**
22 kg
**Volumes**
0.29 m³
**Packaging size**
Length
995 mm
Height
490 mm
Depth
595 mm

### CONSUMPTION AND CONNECTION FEATURES

**Maximum consumption**
280 W
**Voltage**
220-240V
**Frequency**
50-60Hz
**Plug type**
Shuko

### MOTOR TECHNICAL SHEET

**Maximum capacity**
680 m³/h
I.E.C. 61591
**Maximum noise level**
68 dB(A)re1pW
I.E.C.60704-2-13
**Maximum pressure (Pa)**
510 Pa
**Max. motor power**
224 W
**ENERGY CLASS**
B



falmec

## PRESTIGE

**Version**
Wall 65 cm - Black - 800 m3/h


**Collection**
Design+

**EAN code**
8034122329116

## MOTOR TECHNICAL SHEET

| Motor speed | 1 | 2 | 3 | 4 |
|---|---|---|---|---|
| Noise level dB(A)re1pW-I.E.C.60704-2-13 | 54 | 57 | 63 | 68 |
| Capacity (m3/h) I.E.C.61591 | 270 | 370 | 490 | 680 |
| Maximum pressure (Pa) | 390 | 440 | 490 | 510 |
| Motor Power (W) | 130 | 150 | 178 | 224 |
| Air outlet | 150 | 150 | 150 | 150 |

## CAPACITY / PRESSURE



falmec


**PRESTIGE**

**Version**
Wall 65 cm - Black - 800 m3/h

**Collection**
Design+

**EAN code**
8034122329116

**ENERGY LABEL**




| PF | | |
|---|---|---|
| S | Falmec Spa | |
| M | Wall 65 cm - Black - 800 m3/h | |
| AEC | 68,7 | kWh/a |
| EEC | B | |
| FDE | 26,6 | |
| FDEC | B | |
| LE | 9,4 | |
| LEC | E | |
| GFE | 79,0 | |
| GFEC | C | |
| Qmin | 270,0 | m³/h |
| Qmax | 490,0 | m³/h |
| Qboost | 680,0 | m³/h |
| SPEmin | 54 | dBa |
| SPEmax | 63 | dBa |
| SPEboost | 68 | dBa |
| PO | - | W |
| PS | 0,48 | W |
| **PI** | | |
| F | 1 | |
| EEI | 63,3 | |
| Qbep | 357,0 | m³/h |
| Pbep | 404 | Pa |
| Qboost | 680,0 | m³/h |
| Wbep | 150,6 | W |
| WL | 18,80 | W |
| Emiddle | 176 | lex |
| Lwa-SPEmax | 63 | dBa |

**PF_Product fiche according to 65/2014** S_Supplier name / M_Model identification / AEC_Annual Energy Consumption (AEC hood) / EEC_Energy Efficiency class / FDE_Fluid Dynamic Efficiency (FDE hood) / FDEC_Fluid Dynamic Efficiency class / LE_Lighting Efficiency (LE hood) / LEC_Lighting Efficiency class / GFE_Grease Filtering Efficiency / GFEC_Grease Filtering Efficiency class / Qmin_Air flow (in m³/h) at min speed in normal use / Qmax_Air flow (in m³/h) at max speed in normal use / Qboost_Air flow (in m³/h) at intensive or boost setting (max air-flow) / SPEmin_Airborne acoustical A-weighted sound power emissions at min speed in normal use / SPEmax_Airborne acoustical A-weighted sound power emissions at max speed in normal use / SPEboost_Airbone acoustical A-weighted sound power emissions (in dB) at intensive or boost setting / P0_Power consumption in off mode (Po) / Ps_Power consumption in stand by mode (Ps). **PI_Additional information according to 66/2014** F_Time increase factor / EEI_Energy Efficiency Index / Qbep_Measured air flow rate at best efficiency point / Pbep_Measured air pressure at best efficiency point / Qboost_Maximun air flow / Wbep_Measured electric power input at best efficiency point / WL_Nominal power of the lighting system / Emiddle_Average illumination of the lighting system on the cooking surface / Lwa=SPEmax_Sound pressure level at the highest speed.