

CONCORDE

Versiune
Perete 60 cm - 800 m3/h

Colectie
Design

Cod EAN
8034122305035



Fotografie cu caracter strict orientativ
Aceasta poate sa nu corespunda versiunii selectate

CARACTERISTICI

Scotch brite stainless steel (AISI 304)
Aspiratie perimetrala
Control electronic
Iluminare cu LED
Filtru de grasime metalic, detasabil si lavabil
Filtru de carbon inclus

ACCESORII OPTIONALE

KACL.770#41F
Motor de acoperis 1100 m3/h
Brushless
KACL.786#41F
Motor de exterior 1000 m3/h
KACL.796#4AF
Motor de exterior 1500 m3/h
KACL.797#4AF
Motor de acoperis 1300 m3/h
KACL.798#41F
Motor de acoperis 950 m3/h
KACL.815
Lavete pentru curatare inox (cutie 10 buc)

CARACTERISTICI TEHNICE

Tip de instalare
De perete
Dimensiuni
60 cm
Finisaj
Inox Scotch Brite (AISI 304)
Motor
800 m³/h
Tipul panoului de control
Control electronic
Setari de viteza
4
Iluminare
LED 2x1,2 W - 3200 K
Filtru
Filtru metalic "Base" - 235x245 mm
Filtru de Carbon
Filtru de carbon rectangular - Tip 3 (inclus)
Distanta minima
Plita cu gaz: 60 cm
Plita electrica: 52 cm

AMBALARE: GREUTATE SI VOLUM


Greutate bruta
22 kg
Greutate neta
19 kg
Volum
0.27 m³
Dimensiuni ambalaj
Lungime
710 mm
Inaltime
640 mm
Adancime
595 mm

CARACTERISTICI CONSUM SI CONEXIUNE

Consum maxim
280 W
Curent
220-240V
Frecventa
50-60Hz
Tip stecher
Shuko

FISA TEHNICA MOTOR

Capacitate maxima
670 m³/h
I.E.C. 61591
Nivel de zgomot maxim
67 dB(A)re1pW
I.E.C.60704-2-13
Presiune maxima (Pa)
500 Pa
Putere maxima motor
215 W
CLASA DE ENERGIE
B



CONCORDE

Versiune
Perete 60 cm - 800 m3/h


Colectie
Design

Cod EAN
8034122305035

FISA TEHNICA MOTOR

Viteza motorului	1	2	3	4
Nivel de zgomot dB(A)re1pW-I.E.C.60704-2-13	49	55	61	67
Capacitate (m3/h) I.E.C.61591	270	360	470	670
Presiune maxima (Pa)	390	420	460	500
Putere motor (W)	134	156	180	215
Evacuare aer	150	150	150	150

CAPACITATE/ PRESIUNE



CONCORDE

Versiune
Perete 60 cm - 800 m3/h

Colectie
Design

Cod EAN
8034122305035

ETICHETA DE ENERGIE

