

NUVOLA 140

Version

Remote under-roof motor 950 m³/h

Collection

Design+

EAN code

8034122363172



*The photograph is purely for information
It may not correspond to the selected version.*

FEATURES

Perimeter suction
Electronic control
Metallic grease filter, removable and washable
Remote control included
Dynamic LED Light (2700K - 5600K)
Motor sold separately

Cut-out size: 590 x 1325 mm

OPTIONAL ACCESSORIES

KACL.396

Ø200 - Flange

KACL.398

Ø150 - Flange

KACL.770#41F

Remote under-roof 1100 m³/h

Brushless

KACL.782#49F

Slim motor 800 m³/h

KACL.786#41F

Outdoor extractor fan 1000 m³/h

KACL.796#4AF

Outdoor extractor fan 1500 m³/h

KACL.797#4AF

Remote under-roof motor 1300 m³/h

KACL.798#41F

Remote under-roof motor 950 m³/h

KACL.928

Filters spare

KACL.931

Filters Carbon.Zeo - Spare

KACL.939#BF

Ceiling re-circulation filtering kit (only for Slim Motor)

KACL.953#BF

Carbon.Zeo vertical outlet ceiling filter unit kit

TECHNICAL FEATURES

Installation type

Ceiling

Dimensions

140 cm

Finishing

Painted white steel

Type of control

Electronic control

Lighting

Led 4x11 W - 2700 K / 5600 K

Filter

4 x Metallic filter "Base" - 290x267 mm

Maximum distance

Gas hob: 150 cm

Electric hob: 150 cm

PACKAGING:WEIGHTS AND VOLUMES

NUVOLA 140 Gross weight

45.4 kg

Net weight

40.1 kg

Volumes

0.22 m³

Packaging size

Length

1455 mm

Height

210 mm

Depth

730 mm

REMOTE MOTOR Remote under-roof motor 950 m³/h

Gross weight

10 kg

Net weight

9 kg

Volumes

0.06 m³

Packaging size

Length

435 mm

Height

340 mm

Depth

385 mm

CONSUMPTION AND CONNECTION FEATURES

Maximum consumption

50 W

Voltage

220-240V

Frequency

50-60Hz

Plug type

Schuko

MOTOR TECHNICAL SHEET

Maximum capacity

695 m³/h

I.E.C. 61591

Maximum noise level

66 dB(A)re1pW

I.E.C.60704-2-13

Maximum pressure (Pa)


590 Pa

Max. motor power

270 W

ENERGY CLASS

C



Nuvola Led 140 - under roof motor

NUVOLA 140

Version

Remote under-roof motor 950
m³/h

Collection

Design+


EAN code

8034122363172

MOTOR TECHNICAL SHEET

Motor speed	1	2	3	4
Noise level dB(A)re1pW-I.E.C.60704-2-13	48	56	62	66
Capacity (m ³ /h) I.E.C.61591	369	480	600	695
Maximum pressure (Pa)	510	520	560	590
Motor Power (W)	190	220	250	270
Air outlet	150	150	150	150

CAPACITY / PRESSURE



NUVOLA 140

Version

Remote under-roof motor 950
m³/h


Collection

Design+

EAN code

8034122363172

ENERGY LABEL



PF		
S	Falmec Spa	
M	Remote under-roof motor 950 m ³ /h	
AEC	93,8	kWh/a
EEC	C	
FDE	28,1	
FDEC	A	
LE	14,1	
LEC	D	
GFE	65,1	
GFEC	D	
Qmin	365,0	m ³ /h
Qmax	600,0	m ³ /h
Qboost	695,0	m ³ /h
SPEmin	48	dBa
SPEmax	62	dBa
SPEboost	66	dBa
PO	-	W
PS	0,48	W
PI		
F	1	
EEL	72,6	
Qbep	384,0	m ³ /h
Pbep	414	Pa
Qboost	695,0	m ³ /h
Wbep	157,0	W
WL	50,00	W
Emiddle	705	lex
Lwa-SPEmax	62	dBa

PF_Product fiche according to 65/2014 S_Supplier name / M_Model identification / AEC_Annual Energy Consumption (AEC hood) / EEC_Energy Efficiency class / FDE_Fluid Dynamic Efficiency (FDE hood) / FDEC_Fluid Dynamic Efficiency class / LE_Lighting Efficiency (LE hood) / LEC_Lighting Efficiency class / GFE_Grease Filtering Efficiency / GFEC_Grease Filtering Efficiency class / Qmin_Air flow (in m³/h) at min speed in normal use / Qmax_Air flow (in m³/h) at max speed in normal use / Qboost_Air flow (in m³/h) at intensive or boost setting (max air-flow) / SPEmin_Airborne acoustical A-weighted sound power emissions at min speed in normal use / SPEmax_Airborne acoustical A-weighted sound power emissions at max speed in normal use / SPEboost_Airborne acoustical A-weighted sound power emissions (in dB) at intensive or boost setting / PO_Power consumption in off mode (Po) / Ps_Power consumption in stand by mode (Ps). **PI_Additional information according to 66/2014** F_Time increase factor / EEL_Energy Efficiency Index / Qbep_Measured air flow rate at best efficiency point / Pbep_Measured air pressure at best efficiency point / Qboost_Maximum air flow / Wbep_Measured electric power input at best efficiency point / WL_Nominal power of the lighting system / Emiddle_Average illumination of the lighting system on the cooking surface / Lwa-SPEmax_Sound pressure level at the highest speed.