falmec

VIRGOLA

Version
Built-in 120 cm - 600 m3/h

Collection
Design

EAN code
8034122345246



The photograph is purely for information
It may not correspond to the selected version.

FEATURES

Glass panel
Electronic control
Metallic grease filter, removable and washable
Charcoal filter included
Dynamic LED Light (2700K - 5600K)

OPTIONAL ACCESSORIES

KACL.815
Protective cleaning cloths for stainless steel (box 10 pcs)
KCVJN.00#3
Telescopic chimney h 185 + h 185
KCVJN.01#3
Chimney h 120 mm
103050107
Square charcoal filter - Type 3

TECHNICAL FEATURES

Installation type
Built-in
Dimensions
120 cm
Finishing
Tempered turning glass
Scotch brite stainless steel
Motor
600 m³/h
Type of control
Electronic control
Speed settings
3
Lighting
Led 4x1,2 W - 3200 K
Filter
4 x Metallic filter "Base" - 278x207 mm
Charcoal filter
Square charcoal filter - Type 3 (included)
Minimum distance
Gas hob: 52 cm
Electric hob: 52 cm

PACKAGING:WEIGHTS AND VOLUMES


Gross weight
18.1 kg
Net weight
14 kg
Volumes
0.25 m³
Packaging size
Length
1295 mm
Height
410 mm
Depth
465 mm


CONSUMPTION AND CONNECTION FEATURES

Maximum consumption
230 W
Voltage
220-240V
Frequency
50-60Hz
Plug type
Shuko

MOTOR TECHNICAL SHEET

Maximum capacity
480 m³/h
I.E.C. 61591
Maximum noise level
65 dB(A)re1pW
I.E.C.60704-2-13
Maximum pressure (Pa)
500 Pa
Max. motor power
180 W
ENERGY CLASS
C





falmec

VIRGOLA

Version
Built-in 120 cm - 600 m3/h


Collection
Design

EAN code
8034122345246

MOTOR TECHNICAL SHEET

Motor speed	1	2	3
Noise level dB(A)re1pW-I.E.C.60704-2-13	49	58	65
Capacity (m3/h) I.E.C.61591	220	320	480
Maximum pressure (Pa)	270	400	500
Motor Power (W)	100	130	180
Air outlet	120	120	120

CAPACITY / PRESSURE



falmec


VIRGOLA

Version
Built-in 120 cm - 600 m3/h

Collection
Design

EAN code
8034122345246

ENERGY LABEL



PF		
S	Falmec Spa	
M	Built-in 120 cm - 600 m3/h	
AEC	90,2	kWh/a
EEC	C	
FDE	15,8	
FDEC	D	
LE	31,4	
LEC	A	
GFE	80,0	
GFEC	C	
Qmin	220,0	m³/h
Qmax	480,0	m³/h
Qboost	480,0	m³/h
SPEmin	49	dBa
SPEmax	65	dBa
SPEboost	-	dBa
PO	-	W
PS	0,48	W
PI		
F	1.4	
EEI	81,8	
Qbep	303,0	m³/h
Pbep	308	Pa
Qboost	480,0	m³/h
Wbep	164,0	W
WL	8,60	W
Emiddle	270	lex
Lwa-SPEmax	65	dBa

PF_Product fiche according to 65/2014 S_Supplier name / M_Model identification / AEC_Annual Energy Consumption (AEC hood) / EEC_Energy Efficiency class / FDE_Fluid Dynamic Efficiency (FDE hood) / FDEC_Fluid Dynamic Efficiency class / LE_Lighting Efficiency (LE hood) / LEC_Lighting Efficiency class / GFE_Grease Filtering Efficiency / GFEC_Grease Filtering Efficiency class / Qmin_Air flow (in m³/h) at min speed in normal use / Qmax_Air flow (in m³/h) at max speed in normal use / Qboost_Air flow (in m³/h) at intensive or boost setting (max air-flow) / SPEmin_Airborne acoustical A-weighted sound power emissions at min speed in normal use / SPEmax_Airborne acoustical A-weighted sound power emissions at max speed in normal use / SPEboost_Airbone acoustical A-weighted sound power emissions (in dB) at intensive or boost setting / P0_Power consumption in off mode (Po) / Ps_Power consumption in stand by mode (Ps). **PI_Additional information according to 66/2014** F_Time increase factor / EEI_Energy Efficiency Index / Qbep_Measured air flow rate at best efficiency point / Pbep_Measured air pressure at best efficiency point / Qboost_Maximun air flow / Wbep_Measured electric power input at best efficiency point / WL_Nominal power of the lighting system / Emiddle_Average illumination of the lighting system on the cooking surface / Lwa=SPEmax_Sound pressure level at the highest speed.