

GRUPPO INCASSO A+

Version
Built-in 70 cm - 800 m3/h

Collection
A+

EAN code
8034122355191

FEATURES

Scotch brite stainless steel (AISI 304)
Perimeter suction
Electronic control
LED lighting
Charcoal filter included
Optional remote control
Dynamic LED Light (2700K - 5600K)

OPTIONAL ACCESSORIES

KACL.815
Protective cleaning cloths for stainless steel (box 10 pcs)
105080053
Remote control

TECHNICAL FEATURES

Installation type
Built-in
Dimensions
70 cm
Finishing
Scotch brite stainless steel (AISI 304)
Motor
1700 m³/h
Type of control
Electronic control
Speed settings
3
Lighting
Led 2x1,2 W - 3200 K
Filter
3 x Metallic filter "Base" - 204x207 mm
Charcoal filter
Round charcoal filter Ø170 mm - Type 6 (included)
Minimum distance
Gas hob: 62 cm
Electric hob: 52 cm

PACKAGING:WEIGHTS AND VOLUMES



Gross weight
12 kg
Net weight
9.4 kg
Volumes
0.12 m³
Packaging size
Length
855 mm
Height
380 mm
Depth
375 mm

CONSUMPTION AND CONNECTION FEATURES

Maximum consumption
150 W
Voltage
220-240V
Frequency
50-60Hz
Plug type
Shuko

MOTOR TECHNICAL SHEET

Maximum capacity
720 m³/h
I.E.C. 61591
Maximum noise level
66 dB(A)re1pW
I.E.C.60704-2-13
Maximum pressure (Pa)
510 Pa
Max. motor power
130 W
ENERGY CLASS
A+



GRUPPO INCASSO A+

Version

Built-in 70 cm - 800 m3/h

Collection

A+

EAN code

8034122355191

MOTOR TECHNICAL SHEET

Motor speed	1	2	3	4
Noise level dB(A)re1pW-I.E.C.60704-2-13	46	52	58	66
Capacity (m3/h) I.E.C.61591	280	380	480	720
Maximum pressure (Pa)	390	440	490	510
Motor Power (W)	15	55	90	130
Air outlet	150	150	150	150


GRUPPO INCASSO A+

Version
Built-in 70 cm - 800 m3/h

Collection
A+

EAN code
8034122355191

ENERGY LABEL



PF		
S	Falmec Spa	
M	Built-in 70 cm - 800 m3/h	
AEC	27,6	kWh/a
EEC	A+	
FDE	35,0	
FDEC	A	
LE	30,1	
LEC	A	
GFE	80,0	
GFEC	C	
Qmin	280,0	m³/h
Qmax	480,0	m³/h
Qboost	720,0	m³/h
SPEmin	46	dBa
SPEmax	58	dBa
SPEboost	66	dBa
PO	-	W
PS	0,48	W
PI		
F	0.7	
EEL	38,4	
Qbep	332,0	m³/h
Pbep	380	Pa
Qboost	720,0	m³/h
Wbep	100,0	W
WL	2,80	W
Emiddle	85	lex
Lwa-SPEmax	58	dBa

PF_Product fiche according to 65/2014 S_Supplier name / M_Model identification / AEC_Annual Energy Consumption (AEC hood) / EEC_Energy Efficiency class / FDE_Fluid Dynamic Efficiency (FDE hood) / FDEC_Fluid Dynamic Efficiency class / LE_Lighting Efficiency (LE hood) / LEC_Lighting Efficiency class / GFE_Grease Filtering Efficiency / GFEC_Grease Filtering Efficiency class / Qmin_Air flow (in m³/h) at min speed in normal use / Qmax_Air flow (in m³/h) at max speed in normal use / Qboost_Air flow (in m³/h) at intensive or boost setting (max air-flow) / SPEmin_Airborne acoustical A-weighted sound power emissions at min speed in normal use / SPEmax_Airborne acoustical A-weighted sound power emissions at max speed in normal use / SPEboost_Airborne acoustical A-weighted sound power emissions (in dB) at intensive or boost setting / PO_Power consumption in off mode (Po) / Ps_Power consumption in stand by mode (Ps). PI_Additional information according to 66/2014 F_Time increase factor / EEL_Energy Efficiency Index / Qbep_Measured air flow rate at best efficiency point / Pbep_Measured air pressure at best efficiency point / Qboost_Maximun air flow / Wbep_Measured electric power input at best efficiency point / WL_Nominal power of the lighting system / Emiddle_Average illumination of the lighting system on the cooking surface / Lwa=SPEmax_Sound pressure level at the highest speed.