

QUASAR TOP A+

Version
Wall 90 cm - Fasteel - 800
m3/h

Collection
A+

EAN code
8034122205601



The photograph is purely for information
It may not correspond to the selected version.

FEATURES

- Perimeter suction
- Electronic control
- LED lighting
- Metallic grease filter, removable and washable
- Optional combined regenerable Carbon.Zeo filter
- Charcoal filter included
- Possible to duct wall mounted from rear
- Optional Chimney

OPTIONAL ACCESSORIES

- KACL.941**
External filter unit for sloped hoods
- KCQAN.00#X**
Chimney (Fasteel)

TECHNICAL FEATURES



- Installation type**
Wall
- Dimensions**
90 cm
- Finishing**
Scotch brite Fasteel no finger prints
- Motor**
1700 m³/h
- Type of control**
Electronic control
- Speed settings**
4
- Lighting**
Led 3x1,2 W - 3200 K
- Filter**
2 x Metallic filter "Base" - 290x326 mm
- Charcoal filter**
Round charcoal filter Ø170 mm - Type 6 (included)
- Minimum distance**
Gas hob: 52 cm
Electric hob: 52 cm

PACKAGING:WEIGHTS AND VOLUMES

- Gross weight**
34 kg
- Net weight**
28 kg
- Volumes**
0.42 m³
- Packaging size**
Length 1035 mm
Height 550 mm
Depth 740 mm

CONSUMPTION AND CONNECTION FEATURES

- Maximum consumption**
150 W
- Voltage**
220-240V
- Frequency**
50-60Hz
- Plug type**
Shuko
- ENERGY CLASS**
A+




QUASAR TOP A+

Version
Wall 90 cm - Fasteel - 800 m3/h

Collection
A+

EAN code
8034122205601

ENERGY LABEL



PF		
S	Falmec Spa	
M	Wall 90 cm - Fasteel - 800 m3/h	
AEC	28,6	kWh/a
EEC	A+	
FDE	35,0	
FDEC	A	
LE	29,5	
LEC	A	
GFE	60,0	
GFEC	E	
Qmin	280,0	m³/h
Qmax	480,0	m³/h
Qboost	720,0	m³/h
SPEmin	46	dBa
SPEmax	58	dBa
SPEboost	66	dBa
PO	-	W
PS	0,48	W
PI		
F	0.7	
EEL	39,4	
Qbep	332,0	m³/h
Pbep	380	Pa
Qboost	720,0	m³/h
Wbep	100,0	W
WL	4,20	W
Emiddle	124	lex
Lwa-SPEmax	58	dBa

PF_Product fiche according to 65/2014 S_Supplier name / M_Model identification / AEC_Annual Energy Consumption (AEC hood) / EEC_Energy Efficiency class / FDE_Fluid Dynamic Efficiency (FDE hood) / FDEC_Fluid Dynamic Efficiency class / LE_Lighting Efficiency (LE hood) / LEC_Lighting Efficiency class / GFE_Grease Filtering Efficiency / GFEC_Grease Filtering Efficiency class / Qmin_Air flow (in m³/h) at min speed in normal use / Qmax_Air flow (in m³/h) at max speed in normal use / Qboost_Air flow (in m³/h) at intensive or boost setting (max air-flow) / SPEmin_Airborne acoustical A-weighted sound power emissions at min speed in normal use / SPEmax_Airborne acoustical A-weighted sound power emissions at max speed in normal use / SPEboost_Airborne acoustical A-weighted sound power emissions (in dB) at intensive or boost setting / PO_Power consumption in off mode (Po) / Ps_Power consumption in stand by mode (Ps). PI_Additional information according to 66/2014 F_Time increase factor / EEL_Energy Efficiency Index / Qbep_Measured air flow rate at best efficiency point / Pbep_Measured air pressure at best efficiency point / Qboost_Maximun air flow / Wbep_Measured electric power input at best efficiency point / WL_Nominal power of the lighting system / Emiddle_Average illumination of the lighting system on the cooking surface / Lwa=SPEmax_Sound pressure level at the highest speed.