

STILO NRS

Version

Island 90 cm - Fasteel - 800 m3/h

Collection

Silence - NRS

EAN code

803412235511



The photograph is purely for information
It may not correspond to the selected version.

FEATURES

- Scotch brite stainless steel (AISI 304)
- NRS technology for a quieter kitchen
- Electronic control
- LED lighting
- Metallic grease filter, removable and washable
- Optional charcoal filter
- Frontal element in Fasteel finishing
- Perimeter suction with tempered glass panel

OPTIONAL ACCESSORIES

- KACL.400**
Silent / Conveyor NRS
- KACL.815**
Protective cleaning cloths for stainless steel (box 10 pcs)
- 101078900**
High performance filter

TECHNICAL FEATURES

- Installation type**
Island
- Dimensions**
90 cm
- Finishing**
Scotch brite stainless steel (AISI 304)
- Motor**
800 m³/h
- Type of control**
Electronic control
- Speed settings**
4
- Lighting**
Led 4x1,2 W - 3200 K
- Filter**
2 x Metallic filter "Base" - 274x274 mm
- Charcoal filter**
High performance filter (optional)
- Minimum distance**
Gas hob: 65 cm
Electric hob: 52 cm

PACKAGING:WEIGHTS AND VOLUMES


- Gross weight**
59 kg
- Net weight**
52 kg
- Volumes**
0.62 m³
- Packaging size**
Length
1070 mm
Height
670 mm
Depth
870 mm

CONSUMPTION AND CONNECTION FEATURES

- Maximum consumption**
280 W
- Voltage**
220-240V
- Frequency**
50-60Hz
- Plug type**
Shuko

MOTOR TECHNICAL SHEET

- Maximum capacity**
715 m³/h
I.E.C. 61591
- Maximum noise level**
53 dB(A)re1pW
I.E.C.60704-2-13
- Maximum pressure (Pa)**
510 Pa
- Max. motor power**
224 W
- ENERGY CLASS**
B



STILO NRS

Version
Island 90 cm - Fasteel - 800
m3/h


Collection
Silence - NRS

EAN code
8034122355511

MOTOR TECHNICAL SHEET

Motor speed	1	2	3	4
Noise level dB(A)re1pW-I.E.C.60704-2-13	37	41	45	53
Capacity (m3/h) I.E.C.61591	270	380	490	715
Maximum pressure (Pa)	390	440	490	510
Motor Power (W)	130	150	178	224
Air outlet	150	150	150	150

CAPACITY / PRESSURE




STILO NRS

Version
Island 90 cm - Fasteel - 800
m3/h

Collection
Silence - NRS

EAN code
803412235511

ENERGY LABEL



PF		
S	Falmec Spa	
M	Island 90 cm - Fasteel - 800 m3/h	
AEC	60,3	kWh/a
EEC	B	
FDE	28,1	
FDEC	A	
LE	25,3	
LEC	B	
GFE	53,0	
GFEC	F	
Qmin	270,0	m³/h
Qmax	490,0	m³/h
Qboost	715,0	m³/h
SPEmin	37	dBa
SPEmax	45	dBa
SPEboost	53	dBa
PO	-	W
PS	0,48	W
PI		
F	1	
EEL	58,5	
Qbep	394,0	m³/h
Pbep	395	Pa
Qboost	715,0	m³/h
Wbep	154,0	W
WL	5,60	W
Emiddle	143	lex
Lwa-SPEmax	45	dBa

PF_Product fiche according to 65/2014 S_Supplier name / M_Model identification / AEC_Annual Energy Consumption (AEC hood) / EEC_Energy Efficiency class / FDE_Fluid Dynamic Efficiency (FDE hood) / FDEC_Fluid Dynamic Efficiency class / LE_Lighting Efficiency (LE hood) / LEC_Lighting Efficiency class / GFE_Grease Filtering Efficiency / GFEC_Grease Filtering Efficiency class / Qmin_Air flow (in m³/h) at min speed in normal use / Qmax_Air flow (in m³/h) at max speed in normal use / Qboost_Air flow (in m³/h) at intensive or boost setting (max air-flow) / SPEmin_Airborne acoustical A-weighted sound power emissions at min speed in normal use / SPEmax_Airborne acoustical A-weighted sound power emissions at max speed in normal use / SPEboost_Airborne acoustical A-weighted sound power emissions (in dB) at intensive or boost setting / PO_Power consumption in off mode (Po) / Ps_Power consumption in stand by mode (Ps). PI_Additional information according to 66/2014 F_Time increase factor / EEL_Energy Efficiency Index / Qbep_Measured air flow rate at best efficiency point / Pbep_Measured air pressure at best efficiency point / Qboost_Maximun air flow / Wbep_Measured electric power input at best efficiency point / WL_Nominal power of the lighting system / Emiddle_Average illumination of the lighting system on the cooking surface / Lwa=SPEmax_Sound pressure level at the highest speed.