falmec

TAB A+

Version
Wall 80 cm - White - 800 m3/h

Collection
A+

EAN code
8034122355269



The photograph is purely for information
It may not correspond to the selected version.

FEATURES

White opening frontal
Chrome edge
Electronic control
LED lighting
Top filter, removable and washable
Charcoal filter included
Possible to duct wall mounted from rear
Optional Chimney

OPTIONAL ACCESSORIES

KACL.815
Protective cleaning cloths for stainless steel (box 10 pcs)
KCTCN.001#B
KIT CHIMNEY TAB 60-80 NOR. WHITE

TECHNICAL FEATURES

Installation type
Wall
Dimensions
80 cm
Finishing
White opening frontal
Chrome edge
Motor
1700 m³/h
Type of control
Electronic control
Speed settings
4
Lighting
Led 4x1,2 W - 3200 K
Charcoal filter
Round charcoal filter Ø170 mm - Type 6 (included)
Minimum distance
Gas hob: 53 cm
Electric hob: 52 cm

PACKAGING:WEIGHTS AND VOLUMES


Gross weight
26 kg
Net weight
22 kg
Volumes
0.28 m³
Packaging size
Length
995 mm
Height
480 mm
Depth
595 mm


CONSUMPTION AND CONNECTION FEATURES

Maximum consumption
150 W
Voltage
220-240V
Frequency
50-60Hz
Plug type
Shuko

MOTOR TECHNICAL SHEET

Maximum capacity
720 m³/h
I.E.C. 61591
Maximum noise level
66 dB(A)re1pW
I.E.C.60704-2-13
Maximum pressure (Pa)
510 Pa
Max. motor power
130 W
ENERGY CLASS
A+





falmec

TAB A+

Version
Wall 80 cm - White - 800 m3/h

Collection
A+

EAN code
8034122355269

MOTOR TECHNICAL SHEET

Motor speed	1	2	3	4
Noise level dB(A)re1pW-I.E.C.60704-2-13	46	52	58	66
Capacity (m3/h) I.E.C.61591	280	380	480	720
Maximum pressure (Pa)	390	440	490	510
Motor Power (W)	15	55	90	130
Air outlet	150	150	150	150

falmec


TAB A+

Version
Wall 80 cm - White - 800 m3/h

Collection
A+

EAN code
8034122355269

ENERGY LABEL



PF		
S	Falmec Spa	
M	Wall 80 cm - White - 800 m3/h	
AEC	29,7	kWh/a
EEC	A+	
FDE	35,0	
FDEC	A	
LE	28,1	
LEC	A	
GFE	60,0	
GFEC	E	
Qmin	280,0	m³/h
Qmax	490,0	m³/h
Qboost	720,0	m³/h
SPEmin	46	dBa
SPEmax	58	dBa
SPEboost	66	dBa
PO	-	W
PS	0,48	W
PI		
F	0.7	
EEI	40,5	
Qbep	332,0	m³/h
Pbep	380	Pa
Qboost	720,0	m³/h
Wbep	100,0	W
WL	5,60	W
Emiddle	159	lex
Lwa-SPEmax	58	dBa

PF_Product fiche according to 65/2014 S_Supplier name / M_Model identification / AEC_Annual Energy Consumption (AEC hood) / EEC_Energy Efficiency class / FDE_Fluid Dynamic Efficiency (FDE hood) / FDEC_Fluid Dynamic Efficiency class / LE_Lighting Efficiency (LE hood) / LEC_Lighting Efficiency class / GFE_Grease Filtering Efficiency / GFEC_Grease Filtering Efficiency class / Qmin_Air flow (in m³/h) at min speed in normal use / Qmax_Air flow (in m³/h) at max speed in normal use / Qboost_Air flow (in m³/h) at intensive or boost setting (max air-flow) / SPEmin_Airborne acoustical A-weighted sound power emissions at min speed in normal use / SPEmax_Airborne acoustical A-weighted sound power emissions at max speed in normal use / SPEboost_Airbone acoustical A-weighted sound power emissions (in dB) at intensive or boost setting / P0_Power consumption in off mode (Po) / Ps_Power consumption in stand by mode (Ps). **PI_Additional information according to 66/2014** F_Time increase factor / EEI_Energy Efficiency Index / Qbep_Measured air flow rate at best efficiency point / Pbep_Measured air pressure at best efficiency point / Qboost_Maximun air flow / Wbep_Measured electric power input at best efficiency point / WL_Nominal power of the lighting system / Emiddle_Average illumination of the lighting system on the cooking surface / Lwa=SPEmax_Sound pressure level at the highest speed.