

TAB A+

Version
Wall 80 cm - Black - 800 m3/h

Collection
A+

EAN code
8034122355276



The photograph is purely for information
It may not correspond to the selected version.

FEATURES

- Black opening frontal
- Chrome edge
- Electronic control
- LED lighting
- Top filter, removable and washable
- Remote control included
- Possible to duct wall mounted from rear
- Optional Chimney

OPTIONAL ACCESSORIES

- KACL.815**
Protective cleaning cloths for stainless steel (box 10 pcs)
- KCTCN.001#I**
KIT CHIMNEY TAB 60-80 NOR. STAINLESS STEEL

TECHNICAL FEATURES

- Installation type**
Wall
- Dimensions**
80 cm
- Finishing**
Black opening frontal
Chrome edge
- Motor**
1700 m³/h
- Type of control**
Electronic control
- Speed settings**
4
- Lighting**
Led 4x1,2 W - 3200 K
- Charcoal filter**
Round charcoal filter Ø170 mm - Type 6 (included)
- Minimum distance**
Gas hob: 53 cm
Electric hob: 52 cm

PACKAGING:WEIGHTS AND VOLUMES



- Gross weight**
26 kg
- Net weight**
22 kg
- Volumes**
0.28 m³
- Packaging size**
Length 995 mm
Height 480 mm
Depth 595 mm

CONSUMPTION AND CONNECTION FEATURES

- Maximum consumption**
150 W
- Voltage**
220-240V
- Frequency**
50-60Hz
- Plug type**
Shuko

MOTOR TECHNICAL SHEET

- Maximum capacity**
720 m³/h
I.E.C. 61591
- Maximum noise level**
66 dB(A)re1pW
I.E.C.60704-2-13
- Maximum pressure (Pa)**
510 Pa
- Max. motor power**
130 W
- ENERGY CLASS**
A+



TAB A+

Version

Wall 80 cm - Black - 800 m3/h

Collection

A+

EAN code

8034122355276

MOTOR TECHNICAL SHEET

Motor speed	1	2	3	4
Noise level dB(A)re1pW-I.E.C.60704-2-13	46	52	58	66
Capacity (m3/h) I.E.C.61591	280	380	480	720
Maximum pressure (Pa)	390	440	490	510
Motor Power (W)	15	55	90	130
Air outlet	150	150	150	150


TAB A+

Version
Wall 80 cm - Black - 800 m3/h

Collection
A+

EAN code
8034122355276

ENERGY LABEL



PF		
S	Falmec Spa	
M	Wall 80 cm - Black - 800 m3/h	
AEC	29,7	kWh/a
EEC	A+	
FDE	35,0	
FDEC	A	
LE	28,1	
LEC	A	
GFE	60,0	
GFEC	E	
Qmin	280,0	m³/h
Qmax	490,0	m³/h
Qboost	720,0	m³/h
SPEmin	46	dBa
SPEmax	58	dBa
SPEboost	66	dBa
PO	-	W
PS	0,48	W
PI		
F	0.7	
EEL	40,5	
Qbep	332,0	m³/h
Pbep	380	Pa
Qboost	720,0	m³/h
Wbep	100,0	W
WL	5,60	W
Emiddle	159	lux
Lwa-SPEmax	58	dBa

PF_Product fiche according to 65/2014 S_Supplier name / M_Model identification / AEC_Annual Energy Consumption (AEC hood) / EEC_Energy Efficiency class / FDE_Fluid Dynamic Efficiency (FDE hood) / FDEC_Fluid Dynamic Efficiency class / LE_Lighting Efficiency (LE hood) / LEC_Lighting Efficiency class / GFE_Grease Filtering Efficiency / GFEC_Grease Filtering Efficiency class / Qmin_Air flow (in m³/h) at min speed in normal use / Qmax_Air flow (in m³/h) at max speed in normal use / Qboost_Air flow (in m³/h) at intensive or boost setting (max air-flow) / SPEmin_Airborne acoustical A-weighted sound power emissions at min speed in normal use / SPEmax_Airborne acoustical A-weighted sound power emissions at max speed in normal use / SPEboost_Airbone acoustical A-weighted sound power emissions (in dB) at intensive or boost setting / PO_Power consumption in off mode (Po) / Ps_Power consumption in stand by mode (Ps). PI_Additional information according to 66/2014 F_Time increase factor / EEL_Energy Efficiency Index / Qbep_Measured air flow rate at best efficiency point / Pbep_Measured air pressure at best efficiency point / Qboost_Maximun air flow / Wbep_Measured electric power input at best efficiency point / WL_Nominal power of the lighting system / Emiddle_Average illumination of the lighting system on the cooking surface / Lwa=SPEmax_Sound pressure level at the highest speed.