

## GRUPPO INCASSO NRS

### Version

FNINS20B5SS-R/ Built-in - 19  
11/16" (50 cm) 500 CFM

### Collection

Silence - NRS

### EAN code

8034122350332



Photograph is for information purposes only  
May not correspond to the selected version

## FEATURES

**NRS technology for a quieter kitchen**

**Electronic control**

**Metallic grease filter, removable and washable**

**Combined Carbon.Zeo filter, regenable**

**Remote control (optional)**

**Dynamic Light (2700K - 5600K)**

**SRS Speed reduction system**

Recommended mounting height from cooking surface to hood bottom: 24" - 36"

Availability Carbon.Zeo filter KACL.1039 for hoods produced from Sept. 2024

## OPTIONAL ACCESSORIES

### 105080053

Remote control

### KACL.400

Silent / Conveyor NRS

### KACL.815

Protective cleaning cloths for stainless steel (box 10 pcs)

## TECHNICAL FEATURES

### Installation type

Built-in

### Dimensions

20 / 50 cm

### Finish

Scotch brite stainless steel (AISI 304)

### Motor

500 CFM

### Type of control

Electronic control

### Speed

4

### Lighting

Led 2x1,2 W - 3200 K

### Filter

Top - Gr. Incasso NRS / 50 cm

### Charcoal filter

Carbon.Zeo Microtech filter (optional)

### Minimum distance

Gas hob: 25 in

Electric hob: 21 in

## PACKAGING:WEIGHTS AND VOLUMES

### Gross weight

58 lbs

### Net weight

48 lbs

### Volumes

10 ft<sup>3</sup>

### Packaging size

Length

38 in

Height

17 in

Depth

26 in

## CONSUMPTION AND CONNECTION FEATURES

### Maximum consumption

280 W

### Plug type

Hood comes standard with Nema 5-15P power cord

## MOTOR TECHNICAL SHEET

### Maximum capacity

610 m<sup>3</sup>/h

I.E.C. 61591

### Maximum noise level

54,5 dB(A)re1pW


I.E.C.60704-2-13

### Maximum pressure (Pa)

510 Pa

### Max. motor power

224 W



Cut-out size: 19 15/16" (506) x 10 5/16" (262)

## GRUPPO INCASSO NRS

### Version

FNINS20B5SS-R/ Built-in - 19  
11/16" (50 cm) 500 CFM

### Collection

Silence - NRS

### EAN code

8034122350332

## MOTOR TECHNICAL SHEET

Motor Speed	1	2	3	4
Noise level dB(A)re1pW-I.E.C.60704-2-13	37	41	46	54,5
Capacity (m3/h) I.E.C.61591	220	290	375	610
Maximum pressure (Pa)	390	440	490	510
Power (W)	130	150	178	224
Air outlet	150	150	150	150

CAPACITY / PRESSURE

