

## LUMINA NRS

### Version

FNLUM36W5SS / Wall - 36"  
(90 cm) Steel - 500 CFM

### Collection

Silence - NRS

### EAN code

8034122345888

## FEATURES

**NRS technology for a quieter kitchen**  
**Touch control + 24 h function**  
**White fluorescent ambient light**  
**Metallic grease filter, removable and washable**  
**Optional charcoal filter**

Recommended mounting height from cooking surface to hood bottom: 24" - 35";  
 Availability Carbon.Zeo filter KACL.961/ for hoods produced from 10/22/2020

## OPTIONAL ACCESSORIES

### KACL.400

Silent / Conveyor NRS

### KACL.570#I

Extension H700 - Wall

### KACL.571#I

Extension H960 - Wall

### KACL.815

Protective cleaning cloths for stainless steel (box 10 pcs)

### KACL.961

Charcoal and Zeolite filter

### 101078900

High performance filter

## TECHNICAL FEATURES

### Installation type

Wall

### Dimensions

36 / 90 cm

### Finish

Scotch brite stainless steel (AISI 304)

Tempered glass with white finish

### Motor

500 CFM

### Type of control

Touch control

### Speed settings

4

### Lighting

Fluorescent 1x21 W

### Filter

2 x Metallic filter "Base" - 274x274 mm

### Charcoal filter

High performance filter (optional)

### Minimum distance

Gas hob: 26 in

Electric hob: 21 in

## PACKAGING:WEIGHTS AND VOLUMES

### Gross weight

93 lbs

### Net weight

80 lbs

### Volumes

19 ft<sup>3</sup>

### Packaging size

Length

41 in

Height

27 in

Depth

30 in

## CONSUMPTION AND CONNECTION FEATURES

### Maximum consumption

340 W

### Plug type

Hood comes standard with Nema 5-15P power cord

## MOTOR TECHNICAL SHEET

### Maximum capacity

610 m<sup>3</sup>/h

I.E.C. 61591

### Maximum noise level

55 dB(A)re1pW


I.E.C.60704-2-13

### Maximum pressure (Pa)

582 Pa

### Max. motor power

224 W



## LUMINA NRS

### Version

FNLUM36W5SS / Wall - 36"  
(90 cm) Steel - 500 CFM

### Collection

Silence - NRS

### EAN code

8034122345888

## MOTOR TECHNICAL SHEET

Motor Speed	1	2	3	4
Noise level dB(A)re1pW-I.E.C.60704-2-13	37	41	46	55
Capacity (m3/h) I.E.C.61591	190	300	380	610
Maximum pressure (Pa)	490	500	520	582
Motor Power (W)	130	150	178	224
Air outlet	150	150	150	150

# CAPACITY / PRESSURE

