

LUMINA NRS

Version

FNLNA36W5SS / Wall - 36"
(90 cm) Steel - 500 CFM

Collection

Silence - NRS

EAN code

8034122345888



Photograph is for information purposes only
May not correspond to the selected version

FEATURES

NRS technology for a quieter kitchen
Touch control + 24 h function
White fluorescent ambient light
Fluorescent lighting
Metallic grease filter, removable and washable
Combined Carbon.Zeo filter, regenerable

Recommended mounting height from cooking surface to hood bottom: 24" - 35";

Availability Carbon.Zeo filter KACL.961 for hoods produced from 10/22/2020

Availability Carbon.Zeo filter KACL.1039 for hoods produced from Sept. 2024

OPTIONAL ACCESSORIES

KACL.1039

Carbon.Zeo Microtech filter

KACL.400

Silent / Conveyor NRS

KACL.570#I

Extension H700 Wall - Inox

KACL.571#I

Extension H960 Wall - Inox

KACL.815

Protective cleaning cloths for stainless steel (box 10 pcs)

TECHNICAL FEATURES

Installation type

Wall

Dimensions

36 / 90 cm

Finish

Scotch brite stainless steel (AISI 304)

Tempered glass with white finish

Motor

500 CFM

Type of control

Touch control

Speed

4

Lighting

Fluorescent

Filter

2 x Metallic filter "Base" - 274x274 mm

Charcoal filter

Carbon.Zeo Microtech filter (optional)

Minimum distance

Gas hob: 26 in

Electric hob: 21 in

PACKAGING:WEIGHTS AND VOLUMES

Gross weight

93 lbs

Net weight

80 lbs

Volumes

14 ft³

Packaging size

Length

40 in

Height

26 in

Depth

24 in

CONSUMPTION AND CONNECTION FEATURES

Maximum consumption

280 W

Plug type

Hood comes standard with Nema 5-15P power cord

MOTOR TECHNICAL SHEET

Maximum capacity

610 m³/h

I.E.C. 61591

Maximum noise level

54,5 dB(A)re1pW


I.E.C.60704-2-13

Maximum pressure (Pa)

510 Pa

Max. motor power

224 W



LUMINA NRS

Version

FNLNA36W5SS / Wall - 36"
(90 cm) Steel - 500 CFM

Collection

Silence - NRS

EAN code

8034122345888

MOTOR TECHNICAL SHEET

Motor Speed	1	2	3	4
Noise level dB(A)re1pW-I.E.C.60704-2-13	37	41	46	54,5
Capacity (m3/h) I.E.C.61591	220	290	375	610
Maximum pressure (Pa)	390	440	490	510
Power (W)	130	150	178	224
Air outlet	150	150	150	150

CAPACITY / PRESSURE

