

MIRA

Version
FFMIR16W5FS-R Wall 16" (40 cm) Fasteel – 500 CFM

Collection
Design

EAN code
8034122202297



Photograph is for information purposes only
May not correspond to the selected version

FEATURES

- Scotch brite Fasteel no finger prints
- Perimeter suction
- Electronic control
- LED lighting
- Metallic grease filter, removable and washable
- Charcoal filter (optional)
- SRS Speed reduction system

Recommended mounting height from cooking surface to hood bottom: 24" - 35"

OPTIONAL ACCESSORIES

- FDNUVMTR600**
FDNUVMTR600 - Motor 600 CFM for North America
- FFCHASQC0BL**
FFCHASQC0BL - Square charcoal filter - Type 3

TECHNICAL FEATURES

- Installation type**
Wall
- Dimensions**
40 cm
- Finish**
Scotch brite Fasteel no finger prints
- Motor**
800 m³/h
- Type of control**
Electronic control
- Speed**
4
- Lighting**
Led 2x1,2 W - 3200 K
- Filter**
Metallic filter "Base" - 277x294 mm (spare part)
- Charcoal filter**
FFCHASQC0BL - Square charcoal filter - Type 3 (optional)
- Minimum distance**
Gas hob: 60 cm
Electric hob: 52 cm

PACKAGING:WEIGHTS AND VOLUMES


- Gross weight**
20 kg
- Net weight**
16 kg
- Volumes**
0.28 m³
- Packaging size**
Length
995 mm
Height
480 mm
Depth
595 mm

CONSUMPTION AND CONNECTION FEATURES

- Maximum consumption**
280 W
- Plug type**
Hood comes standard with Nema 5-15P power cord

MOTOR TECHNICAL SHEET

- Maximum capacity**
590 m³/h
I.E.C. 61591
- Maximum noise level**
64 dB(A)re1pW
I.E.C.60704-2-13
- Maximum pressure (Pa)**
500 Pa
- Max. motor power**
203 W
- ENERGY CLASS**



MIRA

Version
FFMIR16W5FS-R Wall 16" (40
cm) Fasteel – 500 CFM

Collection
Design

EAN code
8034122202297

MOTOR TECHNICAL SHEET

Motor Speed	1	2	3	4
Noise level dB(A)re1pW-I.E.C.60704-2-13	45	50	55	64
Capacity (m3/h) I.E.C.61591	230	300	380	590
Maximum pressure (Pa)	390	420	460	500
Power (W)	134	156	180	203
Air outlet	150	150	150	150

CAPACITY / PRESSURE

