falmec

## VERSO

**Version**
White - 55 cm - 800 m3/h

**Collection**
Design

**EAN code**
8034122358758



*The photograph is purely for information*
*It may not correspond to the selected version.*

## FEATURES

**Tempered glass**
**Touch control + 24 h function**
**Metallic grease filter, removable and washable**
**Optional combined regenerable Carbon.Zeo filter**
**Charcoal filter included**
**Possible to duct wall mounted from rear**
**Optional Chimney**
**Dynamic LED Light (2700K - 5600K)**

## OPTIONAL ACCESSORIES

**KACL.770#41F**
Remote under-roof 1100 m3/h Brushless
**KACL.786#41F**
Outdoor extractor fan 1000 m3/h
**KACL.796#4AF**
Outdoor extractor fan 1500 m3/h
**KACL.797#4AF**
Remote under-roof motor 1300 m3/h
**KACL.798#41F**
Remote under-roof motor 950 m3/h
**KACL.941**
External filter unit for sloped hoods
**KCQAN.00#B**
Optional Chimney (White)

## TECHNICAL FEATURES

**Installation type**
Wall
**Dimensions**
55 cm
**Finishing**
White tempered glass
**Motor**
800 m³/h
**Type of control**
Touch control
**Speed settings**
4
**Lighting**
Led 2x1,2 W - 2700 K / 5600 K
**Charcoal filter**
Round charcoal filter Ø170 mm - Type 6 (optional)
**Minimum distance**
Gas hob: 52 cm
Electric hob: 52 cm

## PACKAGING:WEIGHTS AND VOLUMES


**Gross weight**
19.7 kg
**Net weight**
16.2 kg
**Volumes**
0.17 m³
**Packaging size**
Length
710 mm
Height
450 mm
Depth
595 mm


## CONSUMPTION AND CONNECTION FEATURES

**Maximum consumption**
280 W
**Voltage**
220-240V
**Frequency**
50-60Hz
**Plug type**
Shuko

## MOTOR TECHNICAL SHEET

**Maximum capacity**
750 m³/h
I.E.C. 61591
**Maximum noise level**
66 dB(A)re1pW
I.E.C.60704-2-13
**Maximum pressure (Pa)**
510 Pa
**Max. motor power**
224 W
**ENERGY CLASS**
A



falmec

## VERSO

**Version**
White - 55 cm - 800 m3/h


**Collection**
Design

**EAN code**
8034122358758

## MOTOR TECHNICAL SHEET

| Motor speed | 1 | 2 | 3 | 4 |
|---|---|---|---|---|
| Noise level dB(A)re1pW-I.E.C.60704-2-13 | 46 | 53 | 58 | 66 |
| Capacity (m3/h) I.E.C.61591 | 295 | 390 | 500 | 750 |
| Maximum pressure (Pa) | 390 | 440 | 490 | 510 |
| Motor Power (W) | 130 | 150 | 178 | 224 |
| Air outlet | 150 | 150 | 150 | 150 |

## CAPACITY / PRESSURE



falmec


## VERSO

**Version**
White - 55 cm - 800 m3/h

**Collection**
Design

**EAN code**
8034122358758

## ENERGY LABEL




| PF | | |
|---|---|---|
| S | Falmec Spa | |
| M | White - 55 cm - 800 m3/h | |
| AEC | 53,1 | kWh/a |
| EEC | A | |
| FDE | 31,6 | |
| FDEC | A | |
| LE | 21,6 | |
| LEC | B | |
| GFE | 82,0 | |
| GFEC | C | |
| Qmin | 295,0 | m³/h |
| Qmax | 500,0 | m³/h |
| Qboost | 750,0 | m³/h |
| SPEmin | 46 | dBa |
| SPEmax | 58 | dBa |
| SPEboost | 66 | dBa |
| PO | - | W |
| PS | 0,48 | W |

| PI | | |
|---|---|---|
| F | 0.9 | |
| EEI | 52,7 | |
| Qbep | 440,0 | m³/h |
| Pbep | 388 | Pa |
| Qboost | 750,0 | m³/h |
| Wbep | 150,0 | W |
| WL | 5,30 | W |
| Emiddle | 114 | lex |
| Lwa-SPEmax | 58 | dBa |

**PF_Product fiche according to 65/2014** S_Supplier name / M_Model identification / AEC_Annual Energy Consumption (AEC hood) / EEC_Energy Efficiency class / FDE_Fluid Dynamic Efficiency (FDE hood) / FDEC_Fluid Dynamic Efficiency class / LE_Lighting Efficiency (LE hood) / LEC_Lighting Efficiency class / GFE_Grease Filtering Efficiency / GFEC_Grease Filtering Efficiency class / Qmin_Air flow (in m³/h) at min speed in normal use / Qmax_Air flow (in m³/h) at max speed in normal use / Qboost_Air flow (in m³/h) at intensive or boost setting (max air-flow) / SPEmin_Airborne acoustical A-weighted sound power emissions at min speed in normal use / SPEmax_Airborne acoustical A-weighted sound power emissions at max speed in normal use / SPEboost_Airbone acoustical A-weighted sound power emissions (in dB) at intensive or boost setting / P0_Power consumption in off mode (Po) / Ps_Power consumption in stand by mode (Ps). **PI_Additional information according to 66/2014** F_Time increase factor / EEI_Energy Efficiency Index / Qbep_Measured air flow rate at best efficiency point / Pbep_Measured air pressure at best efficiency point / Qboost_Maximun air flow / Wbep_Measured electric power input at best efficiency point / WL_Nominal power of the lighting system / Emiddle_Average illumination of the lighting system on the cooking surface / Lwa=SPEmax_Sound pressure level at the highest speed.