

## SINTESI

### Version

Sintesi - 600 m<sup>3</sup>/h

### Collection

Integrated cooking systems

### EAN code

8034122358918



*The photograph is purely for information  
It may not correspond to the selected version.*

## FEATURES

**4 cooking zones with automatic pots recognition**  
**Residual heat indicators**  
**Integrated remote hood control**

**9 cooking levels + Power function (Over Boost)**  
**Pot detector sensor**  
**Timer / minute minder**  
**Safety switch-off / safety lock function**  
**Pause function**  
**Keeping warm function on 3 temperature levels: 42° keeping / 70° food defrosting / 94° intermediate cooking (pre boiling)**  
**Flex Surface technology**  
**Double Bridge Function**  
**Automatic cut-off timer**  
**Power management system on three levels: 2.8 kw, 3.5 kw, 7.4 kw**  
**AISI 304 Steel frame**  
**Brushless Motor**  
**Touch control with LED display**  
**Carbon.Zeo/Metallic filter maintenance warning**  
**Carbon.Zeo filter maintenance warning**

## TECHNICAL FEATURES

**Installation type**  
Worktop

**Dimensions**  
88x51 cm

**Finishing**  
Scotch brite stainless steel (AISI 304)

**Motor**  
600 m<sup>3</sup>/h

**Type of control**  
Touch control

**Speed settings**  
9

## PACKAGING:WEIGHTS AND VOLUMES

**Gross weight**  
35.20 kg

**Net weight**  
28.80 kg

**Volume**  
0.28 m<sup>3</sup>

**Packaging size**

Length  
980 mm

Height  
780 mm

Depth  
365 mm

## CONSUMPTION AND CONNECTION FEATURES

**Maximum consumption**  
7560 W

**Voltage / Frequency**  
220-240V

50-60Hz

**ENERGY CLASS**  
A++

## OPTIONAL ACCESSORIES

### KACL.931

Filters Carbon.Zeo - Spare

### KACL.951

Underbase Slim filter unit (h60mm)

### KACL.952

Filter replacement (underbase Slim filter unit - h60mm)

### KACL.955

Base grid (underbase Slim filter unit - h60mm)

## SINTESI

### Version

Sintesi - 600 m<sup>3</sup>/h


### Collection

Integrated cooking systems




### EAN code

8034122358918

### Drawers measurements



Side view



## SINTESI

### Version

Sintesi - 600 m<sup>3</sup>/h


### Collection

Integrated cooking systems

### EAN code

8034122358918

## ENERGY LABEL



PF		
<b>S</b>	Falmec Spa	
<b>M</b>	Sintesi - 600 m <sup>3</sup> /h	
<b>AEC</b>	31,5	kWh/a
<b>ECC</b>	A++	
<b>FDE</b>	37,7	
<b>FDEC</b>	A	
<b>LE</b>	0,0	
<b>LEC</b>		
<b>GFE</b>	87,0	
<b>GFEC</b>	B	
<b>Qmin</b>	260,0	m <sup>3</sup> /h
<b>Qmax</b>	480,0	m <sup>3</sup> /h
<b>Qboost</b>	520,0	m <sup>3</sup> /h
<b>SPEmin</b>	48	dBa
<b>SPEmax</b>	66	dBa
<b>SPEboost</b>	69	dBa
<b>PO</b>	-	W
<b>PS</b>	0,48	W
PI		
<b>F</b>	0,6	
<b>EEl</b>	33,3	
<b>Qbep</b>	312,0	m <sup>3</sup> /h
<b>Pbep</b>	627	Pa
<b>Qboost</b>	520,0	m <sup>3</sup> /h
<b>Wbep</b>	144,0	W
<b>WL</b>	0,00	W
<b>Emiddle</b>	0	lux
<b>Lwa-SPEmax</b>	66	dBa

**PF\_Product fiche according to 65/2014** S\_Supplier name / M\_Model identification / AEC\_Annual Energy Consumption (AEC hood) / EEC\_Energy Efficiency class / FDE\_Fluid Dynamic Efficiency (FDE hood) / FDEC\_Fluid Dynamic Efficiency class / LE\_Lighting Efficiency (LE hood) / LEC\_Lighting Efficiency class / GFE\_Grease Filtering Efficiency / GFEC\_Grease Filtering Efficiency class / Qmin\_Air flow (in m<sup>3</sup>/h) at min speed in normal use / Qmax\_Air flow (in m<sup>3</sup>/h) at max speed in normal use / Qboost\_Air flow (in m<sup>3</sup>/h) at intensive or boost setting (max air-flow) / SPEmin\_Airborne acoustical A-weighted sound power emissions at min speed in normal use / SPEmax\_Airborne acoustical A-weighted sound power emissions at max speed in normal use / SPEboost\_Airborne acoustical A-weighted sound power emissions (in dB) at intensive or boost setting / PO\_Power consumption in off mode (Po) / Ps\_Power consumption in stand by mode (Ps). **PI\_Additional information according to 66/2014** F\_Time increase factor / EEl\_Energy Efficiency Index / Qbep\_Measured air flow rate at best efficiency point / Pbep\_Measured air pressure at best efficiency point / Qboost\_Maximum air flow / Wbep\_Measured electric power input at best efficiency point / WL\_Nominal power of the lighting system / Emiddle\_Average illumination of the lighting system on the cooking surface / Lwa=SPEmax\_Sound pressure level at the highest speed.