

MODULA

Version

Modula/M1 Worktop - 84 cm

Collection

Cooking systems

EAN code

8034122359335



*The photograph is purely for information
It may not correspond to the selected version.*

FEATURES

Residual heat indicators
Keep warm function: maximum temperature 70°
9 cooking levels + Power function (Over Boost)
Pot detector sensor
Automatic cut-off timer (for each cooking zone)
Timer / minute minder
Safety switch-off / safety lock function
Brushless Motor
Touch control with LED display
Carbon.Zeo/Metallic filter maintenance warning
Motorized flap system
Cooking areas with Flex Surface Technology
Bridge function

TECHNICAL FEATURES

Installation type
Worktop
Dimensions
84 cm
Finishing
Schott black ceramic glass
Motor
600 m³/h
Type of control
Touch control
Speed settings
9

PACKAGING:WEIGHTS AND VOLUMES

Gross weight
32.3 kg
Net weight
26.9 kg
Volumes
0.24 m³
Packaging size
Length
1055 mm
Height
375 mm
Depth
610 mm

CONSUMPTION AND CONNECTION FEATURES

Maximum consumption
7160 W
Voltage
220-240V
Frequency
50-60Hz
ENERGY CLASS
A+

OPTIONAL ACCESSORIES

KACL.930

Kit filters Carbon.Zeo

KACL.931

Filters Carbon.Zeo - Spare

KACL.951


Underbase Slim filter unit (h60mm)

KACL.952


Filter replacement (underbase Slim filter unit - h60mm)

KACL.955



Base grid (underbase Slim filter unit - h60mm)




All versions: side view



Modula/M1: 38 cm Induction Hob x 2



flush installation



over top installation

MODULA

Version

Modula/M1 Worktop - 84 cm


Collection

Cooking systems

EAN code

8034122359335

ENERGY LABEL



PF		
S	Falmec Spa	
M	Modula/M1 Worktop - 84 cm	
AEC	38,3	kWh/a
EEC	A+	
FDE	33,1	
FDEC	A	
LE	0,0	
LEC		
GFE	87,0	
GFEC	B	
Qmin	170,0	m ³ /h
Qmax	380,0	m ³ /h
Qboost	440,0	m ³ /h
SPEmin	46	dBa
SPEmax	64	dBa
SPEboost	67	dBa
PO	-	W
PS	0,48	W
PI		
F	0.8	
EEL	43,8	
Qbep	267,0	m ³ /h
Pbep	584	Pa
Qboost	440,0	m ³ /h
Wbep	131,0	W
WL	0,00	W
Emiddle	0	lx
Lwa-SPEmax	64	dBa

PF_Product fiche according to 65/2014 S_Supplier name / M_Model identification / AEC_Annual Energy Consumption (AEC hood) / EEC_Energy Efficiency class / FDE_Fluid Dynamic Efficiency (FDE hood) / FDEC_Fluid Dynamic Efficiency class / LE_Lighting Efficiency (LE hood) / LEC_Lighting Efficiency class / GFE_Grease Filtering Efficiency / GFEC_Grease Filtering Efficiency class / Qmin_Air flow (in m³/h) at min speed in normal use / Qmax_Air flow (in m³/h) at max speed in normal use / Qboost_Air flow (in m³/h) at intensive or boost setting (max air-flow) / SPEmin_Airborne acoustical A-weighted sound power emissions at min speed in normal use / SPEmax_Airborne acoustical A-weighted sound power emissions at max speed in normal use / SPEboost_Airborne acoustical A-weighted sound power emissions (in dB) at intensive or boost setting / PO_Power consumption in off mode (Po) / Ps_Power consumption in stand by mode (Ps). **PI_Additional information according to 66/2014** F_Time increase factor / EEL_Energy Efficiency Index / Qbep_Measured air flow rate at best efficiency point / Pbep_Measured air pressure at best efficiency point / Qboost_Maximum air flow / Wbep_Measured electric power input at best efficiency point / WL_Nominal power of the lighting system / Emiddle_Average illumination of the lighting system on the cooking surface / Lwa=SPEmax_Sound pressure level at the highest speed.