

PRISMA

Version

FDPRI36W5SW wall 36"/85 cm
- 500CFM - Stainless and
White Glass

Collection

Design+

EAN code

8034122359120



Photograph is for information purposes only
May not correspond to the selected version

FEATURES

Touch control + 24 h function
LED ambient light
LED lighting
Top filter, removable and washable
Combined regenerable Carbon.Zeo filter (optional)
Charcoal filter
Possible to duct wall mounted from rear
Optional Chimney

OPTIONAL ACCESSORIES

FDNUVMTR600

FDNUVMTR600 - Motor 600 CFM for North America

FFCHAR3COBL

FFCHAR3COBL - Round charcoal filter Ø 6' - Type 6

KACL.815

Protective cleaning cloths for stainless steel (box 10 pcs)

KCQAN.00#I

Chimney (Inox)

TECHNICAL FEATURES

Installation type
Wall
Dimensions
36 / 85 cm
Finish
White tempered glass
Motor
500 CFM
Type of control
Touch control
Speed
4

Lighting

Led 2x1,2 W - 3200 K

Ambient lighting

Led 2x1,2 W - 3200 K

Metallic filter

Filter

2 x Metallic filter "Top" - 196x258 mm

Charcoal filter

FFCHAR3COBL - Round charcoal filter Ø 6' - Type 6 (optional)

Minimum distance

Gas hob: 21 in

Electric hob: 21 in

PACKAGING:WEIGHTS AND VOLUMES

Gross weight

60 lbs

Net weight

49 lbs

Volumes

11 ft³

Packaging size

Length

40 in

Height

21 in

Depth

24 in

CONSUMPTION AND CONNECTION FEATURES

Maximum consumption

280 W

MOTOR TECHNICAL SHEET

Maximum capacity

750 m³/h

I.E.C. 61591

Maximum noise level

66 dB(A)re1pW




I.E.C.60704-2-13

Maximum pressure (Pa)

510 Pa

Max. motor power

224 W



PRISMA

Version

FDPRI36W5SW wall 36"/85 cm
- 500CFM - Stainless and
White Glass

Collection

Design+

EAN code

8034122359120

MOTOR TECHNICAL SHEET

Motor Speed	1	2	3	4
Noise level dB(A)re1pW-I.E.C.60704-2-13	46	53	58	66
Capacity (m3/h) I.E.C.61591	295	390	500	750
Maximum pressure (Pa)	390	440	490	510
Power (W)	130	150	178	224
Air outlet	150	150	150	150

CAPACITY / PRESSURE

