

LUMEN NRS

Version
Island - 90 cm - Inox - 800 m3/h

Designer

Collection
Silence - NRS

EAN code
8034122362915

FEATURES


NRS technology for a quieter kitchen
Electronic control
LED lighting
Top filter, removable and washable
Remote control (optional)
Dialogue system with auto mode
Carbon.Zeo Microtech filter (optional)

Dialogue system from 03.04.24

Availability Carbon.Zeo filter KACL.1039 for hoods produced from Sept. 2024


OPTIONAL ACCESSORIES

105080053
Remote control
KACL.1039
Carbon.Zeo Microtech filter
KACL.400
Silent / Conveyer NRS
KACL.572#I
Extension H1200 Island - Inox
KACL.815
Protective cleaning cloths for stainless steel (box 10 pcs)



TECHNICAL FEATURES

Installation type
Island
Dimensions
90 cm
Finishing
Scotch brite stainless steel (AISI 304)
Motor
800 m³/h
Type of control
Electronic control
Speed
3 + boost
Lighting
Strip led (4000K)
Minimum distance
Gas hob: 63 cm
Electric hob: 52 cm



Photograph is for information purposes only
It may not correspond to the selected version.

PACKAGING:WEIGHTS AND VOLUMES

Gross weight
48.2 kg
Net weight
40 kg
Volumes
0.61 m³
Packaging size
Length
1070 mm
Height
660 mm
Depth
870 mm

CONSUMPTION AND CONNECTION FEATURES

Maximum consumption
280 W
Voltage
220-240V
Frequency
50-60Hz

MOTOR TECHNICAL SHEET

Maximum capacity
610 m³/h
I.E.C. 61591
Maximum noise level
54,5 dB(A)re1pW
I.E.C.60704-2-13
Maximum pressure (Pa)
510 Pa
Max. motor power
224 W
ENERGY CLASS
B

LUMEN NRS

Version
Island - 90 cm - Inox - 800
m3/h

Designer


Collection
Silence - NRS

EAN code
8034122362915

MOTOR TECHNICAL SHEET

Motor speed	1	2	3	4
Noise level dB(A)re1pW-I.E.C.60704-2-13	37	41	46	54,5
Capacity (m3/h) I.E.C.61591	220	290	375	610
Maximum pressure (Pa)	390	440	490	510
Power (W)	130	150	178	224
Air outlet	150	150	150	150

CAPACITY / PRESSURE



LUMEN NRS


Version
Island - 90 cm - Inox - 800 m3/h

Designer

Collection
Silence - NRS

EAN code
8034122362915

ENERGY LABEL



PF		
S	Falmec Spa	
M	Island - 90 cm - Inox - 800 m3/h	
AEC	61,0	kWh/a
EEC	B	
FDE	28,9	
FDEC	A	
LE	20,6	
LEC	B	
GFE	80,0	
GFEC	C	
Qmin	220,0	m³/h
Qmax	375,0	m³/h
Qboost	610,0	m³/h
SPEmin	37	dBa
SPEmax	46	dBa
SPEboost	55	dBa
PO	-	W
PS	0,48	W
PI		
F	1	
EEl	62,7	
Qbep	369,0	m³/h
Pbep	369	Pa
Qboost	610,0	m³/h
Wbep	131,0	W
WL	18,00	W
Emiddle	370	lux
Lwa-SPEmax	46	dBa

PF_Product fiche according to 65/2014 S_Supplier name / M_Model identification / AEC_Annual Energy Consumption (AEC hood) / EEC_Energy Efficiency class / FDE_Fluid Dynamic Efficiency (FDE hood) / FDEC_Fluid Dynamic Efficiency class / LE_Lighting Efficiency (LE hood) / LEC_Lighting Efficiency class / GFE_Grease Filtering Efficiency / GFEC_Grease Filtering Efficiency class / Qmin_Air flow (in m³/h) at min speed in normal use / Qmax_Air flow (in m³/h) at max speed in normal use / Qboost_Air flow (in m³/h) at intensive or boost setting (max air-flow) / SPEmin_Airborne acoustical A-weighted sound power emissions at min speed in normal use / SPEmax_Airborne acoustical A-weighted sound power emissions at max speed in normal use / SPEboost_Airborne acoustical A-weighted sound power emissions (in dB) at intensive or boost setting / PO_Power consumption in off mode (Po) / Ps_Power consumption in stand by mode (Ps). **PI_Additional information according to 66/2014** F_Time increase factor / EEl_Energy Efficiency Index / Qbep_Measured air flow rate at best efficiency point /

Pbep_Measured air pressure at best efficiency point / Qboost_Maximun air flow / Wbep_Measured electric power input at best efficiency point / WL_Nominal power of the lighting system / Emiddle_Average illumination of the lighting system on the cooking surface / Lwa=SPEmax_Sound pressure level at the highest speed.