

LIBERTY

Version

Collection

Mirabilia

EAN code

8034122342429



The photograph is purely for information
It may not correspond to the selected version.

FEATURES

- Scotch brite stainless steel (AISI 304)
- Glass
- Perimeter suction
- Electronic control
- LED ambient light
- LED lighting
- Metallic grease filter, removable and washable
- Charcoal filter included
- Possible to duct wall mounted from rear

OPTIONAL ACCESSORIES

- KACL.200**
Pharo - Wall 67 cm
- KACL.202**
Elektra - Wall 67 cm
- KACL.217**
Manhattan - Wall 67 cm
- KACL.575#I**
Extension H700 - Wall
- KACL.576#I**
Extension H960 - Wall
- KACL.770#41F**
Remote under-roof 1100 m3/h
Brushless
- KACL.786#41F**
Outdoor extractor fan 1000 m3/h
- KACL.796#4AF**
Outdoor extractor fan 1500 m3/h
- KACL.797#4AF**
Remote under-roof motor 1300 m3/h
- KACL.798#41F**
Remote under-roof motor 950 m3/h
- KACL.815**
Protective cleaning cloths for stainless steel (box 10 pcs)

TECHNICAL FEATURES


- Installation type**
Wall
- Finishing**
Scotch brite stainless steel (AISI 304)
- Glass
- Motor**
800 m³/h
- Type of control**
Electronic control
- Speed settings**
4
- Lighting**
Led 2x1,2 W - 3200 K
- Ambient lighting**
Ambient led
- Filter**
2 x Metallic filter "Base" - 277x294 mm
- Charcoal filter**
Round charcoal filter Ø170 mm - Type 6 (included)
- Minimum distance**
Gas hob: 60 cm
Electric hob: 52 cm

PACKAGING:WEIGHTS AND VOLUMES

- LIBERTY Gross weight**
22 kg
- Net weight**
18 kg
- Volumes**
0.22 m³
- Packaging size**
Length
915 mm
Height
530 mm
Depth
455 mm
- GLASS KIT Liberty - Wall 67 cm Gross weight**
7.4 kg
- Net weight**
6 kg
- Volumes**
0.07 m³
- Packaging size**
Length
515 mm
Height
440 mm
Depth
320 mm

CONSUMPTION AND CONNECTION FEATURES

- Voltage**
220-240V
- Frequency**
50-60Hz
- Plug type**
Shuko
- MOTOR TECHNICAL SHEET**
Maximum capacity
590 m³/h
I.E.C. 61591
- Maximum noise level**
64 dB(A)re1pW
I.E.C.60704-2-13
- Maximum pressure (Pa)**
500 Pa
- Max. motor power**
203 W
- ENERGY CLASS**
B



LIBERTY

Version

Collection

Mirabilia


EAN code

8034122342429

MOTOR TECHNICAL SHEET

Motor speed	1	2	3	4
Noise level dB(A)re1pW-I.E.C.60704-2-13	45	50	55	64
Capacity (m3/h) I.E.C.61591	230	300	380	590
Maximum pressure (Pa)	390	420	460	500
Motor Power (W)	134	156	180	203
Air outlet	150	150	150	150

CAPACITY / PRESSURE




LIBERTY

Version

Collection
Mirabilia

EAN code
8034122342429

ENERGY LABEL



PF		
S	Falmec Spa	
M		
AEC	55,7	kWh/a
EEC	B	
FDE	25,6	
FDEC	B	
LE	20,5	
LEC	B	
GFE	60,0	
GFEC	E	
Qmin	230,0	m³/h
Qmax	380,0	m³/h
Qboost	590,0	m³/h
SPEmin	45	dBa
SPEmax	55	dBa
SPEboost	64	dBa
PO	-	W
PS	0,48	W
PI		
F	1.1	
EEl	62,4	
Qbep	287,0	m³/h
Pbep	415	Pa
Qboost	590,0	m³/h
Wbep	129,0	W
WL	5,30	W
Emiddle	109	lex
Lwa-SPEmax	55	dBa

PF_Product fiche according to 65/2014 S_Supplier name / M_Model identification / AEC_Annual Energy Consumption (AEC hood) / EEC_Energy Efficiency class / FDE_Fluid Dynamic Efficiency (FDE hood) / FDEC_Fluid Dynamic Efficiency class / LE_Lighting Efficiency (LE hood) / LEC_Lighting Efficiency class / GFE_Grease Filtering Efficiency / GFEC_Grease Filtering Efficiency class / Qmin_Air flow (in m³/h) at min speed in normal use / Qmax_Air flow (in m³/h) at max speed in normal use / Qboost_Air flow (in m³/h) at intensive or boost setting (max air-flow) / SPEmin_Airborne acoustical A-weighted sound power emissions at min speed in normal use / SPEmax_Airborne acoustical A-weighted sound power emissions at max speed in normal use / SPEboost_Airborne acoustical A-weighted sound power emissions (in dB) at intensive or boost setting / PO_Power consumption in off mode (Po) / Ps_Power consumption in stand by mode (Ps). **PI_Additional information according to 66/2014** F_Time increase factor / EEl_Energy Efficiency Index / Qbep_Measured air flow rate at best efficiency point / Pbep_Measured air pressure at best efficiency point / Qboost_Maximun air flow / Wbep_Measured electric power input at best efficiency point / WL_Nominal power of the lighting system / Emiddle_Average illumination of the lighting system on the cooking surface / Lwa=SPEmax_Sound pressure level at the highest speed.