

NEW YORK

Versiune

Colectie
Mirabilia

Cod EAN
8034122342429



CARACTERISTICI

Scotch brite stainless steel
(AISI 304)
Sticla
Aspiratie perimetrala
Control electronic
Iluminare ambientala cu LED
Iluminare cu LED
Filtru de grasime metalic,
detasabil si lavabil
Filtru de carbon inclus
Posibilitatea de a conecta la
tubulatură prin partea din spate

ACCESORII OPTIONALE

KACL.200
Pharo - Perete 67 cm
KACL.202
Elektra - Perete 67 cm
KACL.217
Manhattan - Perete 67 cm
KACL.575#I
Extensie H700 - Perete
KACL.576#I
Extensie H960 - Perete
KACL.770#41F
Motor de acoperis 1100 m3/h
Brushless
KACL.786#41F
Motor de exterior 1000 m3/h
KACL.796#4AF
Motor de exterior 1500 m3/h
KACL.797#4AF
Motor de acoperis 1300 m3/h
KACL.798#41F
Motor de acoperis 950 m3/h
KACL.815
Lavete pentru curatare inox
(cutie 10 buc)

CARACTERISTICI TEHNICE

Tip de instalare
De perete
Finisaj
Inox Scotch Brite (AISI 304)
Sticla
Motor
800 m³/h
Tipul panoului de control
Control electronic
Setari de viteza
4
Iluminare
LED 2x1,2 W - 3200 K
Lumina ambientala
LED ambiental
Filtru
2 x Filtru metalic "Base" -
277x294 mm
Filtru de Carbon
Filtru de carbon rotund Ø170 mm
- Tip 6 (inclus)
Distanta minima
Plita cu gaz: 60 cm
Plita electrica: 52 cm


AMBALARE: GREUTATE SI
VOLUM

NEW YORK Greutate bruta
22 kg
Greutate neta
18 kg
Volum
0.22 m³
Dimensiuni ambalaj
Lungime
915 mm
Inaltime
530 mm
Adancime
455 mm
KIT STICLA New York - Perete
67 cm **Greutate bruta**
7.4 kg
Greutate neta
6 kg
Volum
0.07 m³
Dimensiuni ambalaj
Lungime
515 mm
Inaltime
440 mm
Adancime
320 mm

CARACTERISTICI CONSUM SI
CONEXIUNE

Curent
220-240V
Frecventa
50-60Hz
Tip stecher
Shuko

FISA TEHNICA MOTOR
Capacitate maxima
590 m³/h
I.E.C. 61591
Nivel de zgomot maxim
64 dB(A)re1pW
I.E.C.60704-2-13
Presiune maxima (Pa)
500 Pa
Putere maxima motor
203 W
CLASA DE ENERGIE
B



NEW YORK

Versiune

Colectie

Mirabilia


Cod EAN

8034122342429

FISA TEHNICA MOTOR

Viteza motorului	1	2	3	4
Nivel de zgomot dB(A)re1pW-I.E.C.60704-2-13	45	50	55	64
Capacitate (m3/h) I.E.C.61591	230	300	380	590
Presiune maxima (Pa)	390	420	460	500
Putere motor (W)	134	156	180	203
Evacuare aer	150	150	150	150

CAPACITATE/ PRESIUNE




NEW YORK

Versiune

Colectie
Mirabilia

Cod EAN
8034122342429

ETICHETA DE ENERGIE



PF		
S	Falmec Spa	
M		
AEC	55,7	kWh/a
EEC	B	
FDE	25,6	
FDEC	B	
LE	20,5	
LEC	B	
GFE	60,0	
GFEC	E	
Qmin	230,0	m³/h
Qmax	380,0	m³/h
Qboost	590,0	m³/h
SPEmin	45	dBa
SPEmax	55	dBa
SPEboost	64	dBa
PO	-	W
PS	0,48	W
PI		
F	1.1	
EEl	62,4	
Qbep	287,0	m³/h
Pbep	415	Pa
Qboost	590,0	m³/h
Wbep	129,0	W
WL	5,30	W
Emiddle	109	lex
Lwa-SPEmax	55	dBa