

## PHARO

### Version

### Collection

Mirabilia

### EAN code

8034122342405



The photograph is purely for information  
It may not correspond to the selected version.

## FEATURES

**Scotch brite stainless steel (AISI 304)**  
**Glass**  
**Electronic control**  
**LED ambient light**  
**LED lighting**  
**Metallic grease filter, removable and washable**  
**Possible to duct wall mounted from rear**

## OPTIONAL ACCESSORIES

**KACL.553#I**  
Extension H1200 - Island  
**KACL.770#41F**  
Remote under-roof 1100 m<sup>3</sup>/h  
Brushless  
**KACL.786#41F**  
Outdoor extractor fan 1000 m<sup>3</sup>/h  
**KACL.796#4AF**  
Outdoor extractor fan 1500 m<sup>3</sup>/h  
**KACL.797#4AF**  
Remote under-roof motor 1300 m<sup>3</sup>/h  
**KACL.798#41F**  
Remote under-roof motor 950 m<sup>3</sup>/h  
**KACL.815**  
Protective cleaning cloths for stainless steel (box 10 pcs)

## TECHNICAL FEATURES

**Installation type**  
Island  
**Finishing**  
Scotch brite stainless steel (AISI 304)  
Glass  
**Motor**  
800 m<sup>3</sup>/h  
**Type of control**  
Electronic control  
**Speed settings**  
4  
**Lighting**  
Led 4x1,2 W - 3200 K  
**Ambient lighting**  
Ambient led  
**Filter**  
Metallic filter "Base" - 277x294 mm  
**Charcoal filter**  
Round charcoal filter Ø170 mm - Type 6 (included)  
**Minimum distance**  
Gas hob: 60 cm  
Electric hob: 52 cm

## PACKAGING:WEIGHTS AND VOLUMES


**PHARO Gross weight**  
40 kg  
**Net weight**  
32 kg  
**Volumes**  
0.64 m<sup>3</sup>  
**Packaging size**  
Length  
1035 mm  
Height  
840 mm  
Depth  
740 mm  
**GLASS KIT Pharo - Island 85 cm Gross weight**  
11.4 kg  
**Net weight**  
9 kg  
**Volumes**  
0.15 m<sup>3</sup>  
**Packaging size**  
Length  
620 mm  
Height  
430 mm  
Depth  
545 mm

## CONSUMPTION AND CONNECTION FEATURES

**Voltage**  
220-240V  
**Frequency**  
50-60Hz  
**Plug type**  
Shuko

## MOTOR TECHNICAL SHEET

**Maximum capacity**  
680 m<sup>3</sup>/h  
I.E.C. 61591  
**Maximum noise level**  
68 dB(A)re1pW  
I.E.C.60704-2-13  
**Maximum pressure (Pa)**  
510 Pa  
**Max. motor power**  
224 W  
**ENERGY CLASS**  
B



PHARO

Version

Collection

Mirabilia


EAN code

8034122342405

## MOTOR TECHNICAL SHEET

Motor speed	1	2	3	4
Noise level dB(A)re1pW-I.E.C.60704-2-13	54	57	63	68
Capacity (m3/h) I.E.C.61591	270	370	490	680
Maximum pressure (Pa)	390	440	490	510
Motor Power (W)	130	150	178	224
Air outlet	150	150	150	150

## CAPACITY / PRESSURE



PHARO

Version


Collection

Mirabilia

EAN code

8034122342405

## ENERGY LABEL



		PF	
S	Falmec Spa		
M			
AEC	61,2	kWh/a	
EEC	B		
FDE	26,6		
FDEC	B		
LE	28,4		
LEC	A		
GFE	60,0		
GFEC	E		
Qmin	270,0	m <sup>3</sup> /h	
Qmax	490,0	m <sup>3</sup> /h	
Qboost	680,0	m <sup>3</sup> /h	
SPEmin	54	dBa	
SPEmax	63	dBa	
SPEboost	68	dBa	
PO	-	W	
PS	0,48	W	
		PI	
F	1		
EEl	59,5		
Qbep	357,0	m <sup>3</sup> /h	
Pbep	404	Pa	
Qboost	680,0	m <sup>3</sup> /h	
Wbep	150,6	W	
WL	8,60	W	
Emiddle	245	lux	
Lwa-SPEmax	63	dBa	

**PF\_Product fiche according to 65/2014** S\_Supplier name / M\_Model identification / AEC\_Annual Energy Consumption (AEC hood) / EEC\_Energy Efficiency class / FDE\_Fluid Dynamic Efficiency (FDE hood) / FDEC\_Fluid Dynamic Efficiency class / LE\_Lighting Efficiency (LE hood) / LEC\_Lighting Efficiency class / GFE\_Grease Filtering Efficiency / GFEC\_Grease Filtering Efficiency class / Qmin\_Air flow (in m<sup>3</sup>/h) at min speed in normal use / Qmax\_Air flow (in m<sup>3</sup>/h) at max speed in normal use / Qboost\_Air flow (in m<sup>3</sup>/h) at intensive or boost setting (max air-flow) / SPEmin\_Airborne acoustical A-weighted sound power emissions at min speed in normal use / SPEmax\_Airborne acoustical A-weighted sound power emissions at max speed in normal use / SPEboost\_Airborne acoustical A-weighted sound power emissions (in dB) at intensive or boost setting / PO\_Power consumption in off mode (Po) / Ps\_Power consumption in stand by mode (Ps). **PI\_Additional information according to 66/2014** F\_Time increase factor / EEl\_Energy Efficiency Index / Qbep\_Measured air flow rate at best efficiency point / Pbep\_Measured air pressure at best efficiency point / Qboost\_Maximum air flow / Wbep\_Measured electric power input at best efficiency point / WL\_Nominal power of the lighting system / Emiddle\_Average illumination of the lighting system on the cooking surface / Lwa=SPEmax\_Sound pressure level at the highest speed.